

PRODUCT-DETAILS

CM-PSS.31P

CM-PSS.31P Three-phase monitoring relay
2c/o, 0,0.1-30s, L1-L2-L3=3x380VAC



General Information

Extended Product Type	CM-PSS.31P
Product ID	1SVR740784R2300
EAN	4016779851992
Catalog Description	CM-PSS.31P Three-phase monitoring relay 2c/o, 0,0.1-30s, L1-L2-L3=3x380VAC
Long Description	The CM-PSS.31P relay is from the CM three-phase monitors range. This relay operates with a rated control supply voltage / three-phase measuring voltage of 380 V AC and has a 2 c/o output with contacts rated at 250 V / 4 A. The CM-PSS.31P monitors the phase parameters over/undervoltage and phase failure. Phase sequence monitoring as well as an ON or OFF tripping delay are selectable. The tripping delay is adjustable over a range of instantaneous to 30 s (0, 0.1-30 s). A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC112178D0201
Instructions and Manuals	1SVC730510M0000

Dimensions

Product Net Width	22.5 mm
Product Net Depth / Length	103.7 mm
Product Net Height	85.6 mm
Product Net Weight	0.123 kg

Technical

Function	Phase failure detection Phase sequence monitoring Over- and undervoltage monitoring
Standards	CAN/CSA C22.2 No.14 EN 50581 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508
Measuring Range	(L-L) 342 ... 418 V AC
Rated Control Supply Voltage (U _s)	(L-L) 380 V AC
Rated Frequency (f)	Supply Circuit 50/60 Hz
Output	2 c/o (SPDT) contacts
Time Range	200 ms start-up delay 0 s or 0.1 ... 30 s tripping delay (ON or OFF)
Terminal Type	Screwless Terminals
Rated Operational Current AC-12 (I _e)	(230 V) 4 A
Rated Operational Current AC-15 (I _e)	(230 V) 3 A
Rated Operational Current DC-12 (I _e)	(24 V) 4 A
Rated Operational Current DC-13 (I _e)	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Rated Insulation Voltage (U _i)	Input Circuit / Output Circuit 600 V Output Circuit 1 / Output Circuit 2 300 V
Rated Impulse Withstand Voltage (U _{imp})	Input Circuit 6 kV Output Circuit 4 kV
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Wire Stripping Length	8 mm
Mounting Position	Any
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Environmental

Ambient Air	Operation -25 ... +60 °C
-------------	--------------------------

Temperature	Storage -40 ... +85 °C
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG

Certificates and Declarations (Document Number)

CCC Certificate	CCC_2009010303326655
CQC Certificate	CQC2009010303326655
cULus Certificate	cULus508_20120829-E140448
Declaration of Conformity - CCC	2020980303000197
Declaration of Conformity - CE	1SVD981014
DNV GL Certificate	DNV_GL_TAA000017D
EAC Certificate	EAC_RU_C-DE.ME77.B.03424
Environmental Information	1SAA981020-2401
Instructions and Manuals	1SVC730510M0000
RMRS Certificate	RMRS_1740020250
RoHS Information	1SVD981014

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Height	109 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Gross Weight	0.148 kg
Package Level 1 EAN	4016779851992

Classifications

Object Classification Code	B
ETIM 4	EC001441 - Phase monitoring relay
ETIM 5	EC001441 - Phase monitoring relay
ETIM 6	EC001441 - Phase monitoring relay
ETIM 7	EC001441 - Phase monitoring relay
eClass	V11.0 : 27371803
UNSPSC	39121536
E-Number (Finland)	2712287
E-Number (Sweden)	3860600

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Three Phase Monitors

