

PRODUCT-DETAILS

CM-ENS.31P

CM-ENS.31P Liquid level monitoring relay 2c/o, sensitivity 0.1-1000kOhm



0	Information
General	intormation

Extended Product Type	CM-ENS.31P
Product ID	1SVR740850R0300
EAN	4013614502859

Catalog Description

CM-ENS.31P Liquid level monitoring relay 2c/o, sensitivity 0.1-1000kOhm

rated control supply voltage of 24 - 240 V AC/DC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. It monitors liquid levels of conductive fluids and protects pumps against dry running or tanks against overflow. The working principle as well as the sensitivity can be selected via front-face potentiometers. Furthermore, an ON-delay or an OFF-delay can be adjusted within a range of 0.1 to 10 s. Several electrodes and a sealable transparent cover for protection against unauthorized changes are available as accessory.

The device offers maintenance free Easy Connect Technology with push-in terminals.

The CM-ENS.31P belongs to the CM liquid level monitoring relay range. It operates with a

Long Description

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical 2CDC112230D0201 Information

Instructions and Manuals 1SVC730680M0000

nensions	
uct Net Width	22.5 mm
uct Net Height	85.6 mm
uct Net Depth /	103.7 mm
uct Net Weight	0.134 kg
hnical	
tion	Filling or draining monitoring
suring Range	0,1 1000 kΩ
per of Electrodes	3
d Control Supply ge (U _s)	24 240 V AC/DC
ut	2 c/o (SPDT) contacts
Range 0 s or 0.1	1 30 s tripping delay (ON or OFF)
inal Type	Screwless Terminals
d Operational Current 2 (I _e)	(230 V) 4 A
d Operational Current 5 (I _e)	(230 V) 3 A
d Operational Current 2 (I _e)	(24 V) 4 A
d Operational Current 3 (I _e)	(24 V) 2 A
num Switching city	12 V 10 mA
Outp Supp	suring Circuit / Output Circuit 300 V out Circuit 1 / Output Circuit 2 300 V oly Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V
ge (U _{imp}) Ou	easuring Circuit / Output Circuit 4 kV tput Circuit 1 / Output Circuit 2 4 kV pply Circuit / Measuring Circuit 4 kV Supply Circuit / Output Circuit 4 kV
ee of Protection	Housing IP50 Terminals IP20
voltage Category	III
tion Degree	3
	utput Circuit NC - F Type Fuses 6 A tput Circuit NO - F Type Fuses 10 A
rical Durability	AC-12 100000 cycle
nanical Durability	1000000 cycle
	exible with Ferrule 2x 0.5 1.5 mm² Insulated Ferrule 2x 0.5 1.5 mm² Flexible 2x 0.5 1.5 mm² Rigid 2x 0.5 1.5 mm²
Stripping Length	8 mm
nting Position	Any

Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 EN 50581 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508

echnical UL/CSA	
Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG

Environmental	
Ambient Air Temperature	Operation -25 +60 °C Storage -40 +85 °C
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)	
CCC Certificate	CCC_2015010303819793
CQC Certificate	CQC2015010303819793
cULus Certificate	cULus508_20150627-E140448
Declaration of Conformity - CCC	2020980303000198
Declaration of Conformity - CE	1SVD981005
DNV GL Certificate	DNV_GL_TAA00000RW
EAC Certificate	EAC_RU_C-DE.ME77.B.02330
Instructions and Manuals	1SVC730680M0000
RMRS Certificate	RMRS_1740020250
RoHS Information	1SVD981005

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Height	109 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Gross Weight	0.159 kg
Package Level 1 EAN	4013614502859

Classifications

CM-ENS.31P 4

Object Classification Code	<u>B</u>
ETIM 5	EC001447 - (Fill) level monitoring relay
ETIM 6	EC001447 - (Fill) level monitoring relay
ETIM 7	EC001447 - (Fill) level monitoring relay
eClass	V11.0 : 27371813
E-Number (Finland)	2712573

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products \rightarrow Electronic\ Relays\ and\ Controls \rightarrow Liquid\ Level\ Monitors\ and\ Controls$

