

**TM-I 12 MM BL****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Process reliability: TM-I**

TM-I inlay tags have a guide tab which allows them to slide easily into the transparent sleeves from the type TM. Once the tag is in place, the tab is snapped off at the predetermined break point. The ready-assembled sleeves can then be simply pushed over the conductors. Your benefits: large quantities can be efficiently pre-assembled in a single step.

**General ordering data**

|                    |                                                                                              |
|--------------------|----------------------------------------------------------------------------------------------|
| Version            | TM-I, Insert markers, {Reference (AttributeDefinition) not found: pAttr74196859207437}, blue |
| Order No.          | <a href="#">2005890000</a>                                                                   |
| Type               | TM-I 12 MM BL                                                                                |
| GTIN (EAN)         | 4050118390414                                                                                |
| Qty.               | 2,000 pc(s).                                                                                 |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a>                                        |

Creation date March 26, 2021 8:40:14 PM CET

## TM-I 12 MM BL

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Height         | 12 mm      | Height (inches) | 0.472 inch |
| Net weight     | 0.165 g    | Width           | 4 mm       |
| Width (inches) | 0.157 inch |                 |            |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -40...150 °C |
|-----------------------------|--------------|

## General data

|                                   |              |                                   |        |
|-----------------------------------|--------------|-----------------------------------|--------|
| Colour                            | blue         | Halogen                           | No     |
| Material                          | Polyester    | Number per roll                   | 2,000  |
| Operating temperature range       | -40...150 °C | Operating temperature range, max. | 150 °C |
| Operating temperature range, min. | -40 °C       | UL 94 flammability rating         | HB     |
| Width                             | 4 mm         |                                   |        |

## Conductor and cable markers

|         |    |
|---------|----|
| Halogen | No |
|---------|----|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">STEP</a>                     |
| Engineering Data | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |

### TM-I 12 MM BL

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

