Weidmüller

TM-I 30 MM BL

Process reliability: TM-I

TM-I inlay tags have a guide tab which allows them to slide easily into the transparent sleeves from the type TM. Once the tag is in place, the tab is snapped off at the predetermined break point. The ready-assembled sleeves can then be simply pushed over the conductors. Your benefits: large quantities can be efficiently pre-assembled in a single step.

General ordering data

Version	TM-I, Insert markers, {Reference (AttributeDefinition) not found: pAttr74196859207437}, blue
Order No.	2005990000
Type	TM-I 30 MM BL
GTIN (EAN)	4050118390452
Qty.	2,000 pc(s).
compatible printer	2599430000 2599440000

Creation date March 26, 2021 8:40:47 PM CET

TM-I 30 MM BL

Technical data

Dimensions and weights

Height	30 mm	Height (inches)	1.181 inch
Net weight	0.184 g	Width	4 mm
Width (inches)	0.157 inch		

Temperatures

Operating temperature range	-40...150 °C

General data

Colour	blue	Halogen	No
Material	Polyester	Number per roll	2,000
Operating temperature range	-40...150 °C	Operating temperature range, max.	150 °C
Operating temperature range, min.	-40 °C	UL 94 flammability rating	HB
Width	4 mm		

Conductor and cable markers

Halogen	No

Classifications

ETIM 6.0	EC001530	ETIM 7.0	EC001530
ECLASS 9.0	27-40-04-01	ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01	ECLASS 11.0	27-28-11-02

Approvals

ROHS	Conform

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S

Creation date March 26, 2021 8:40:47 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

2

TM-I 30 MM BL

Drawings

Creation date March 26, 2021 8:40:47 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

3