

PRODUCT-DETAILS

# 204210-1H

## RING TERM CU 12-4 AWG 1/4 STUD DBL



### General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | 204210-1H   |
| Product ID            | 7TAI029020R0000   |
| EAN                   | 5414363111573   |
| Catalog Description   | RING TERM CU 12-4 AWG 1/4 STUD DBL  |
| Long Description      | Insulation Piercing Magnet Wire Ring Terminal, Length 1.58 Inches, Width .81 Inches, Length of Teeth .61 Inches, Width of Teeth .53 Inches, Stud Size 1/4 Inch, Wire Range #12 AWG - #4 AWG 20,760 Circular Mil Area - 104,960 Circular Mil Area, Copper Alloy, Tin Plated, with Double Splices |

### Ordering

|     |               |
|-----|---------------|
| EAN | 5414363111573 |
|-----|---------------|

### Dimensions

|                    |       |
|--------------------|-------|
| Product Net Length | 0, mm |
|--------------------|-------|

### Container Information

|                        |                |
|------------------------|----------------|
| Package Level 1 Units  | 100 piece      |
| Package Level 1 Width  | 5 in<br>127 mm |
| Package Level 1 Height | 4 in           |

|                                |                   |
|--------------------------------|-------------------|
|                                | 102 mm            |
| Package Level 1 Depth / Length | 6 in<br>152 mm    |
| Package Level 2 Units          | 500 piece         |
| Package Level 2 Width          | 6.9 in<br>175 mm  |
| Package Level 2 Height         | 5.1 in<br>130 mm  |
| Package Level 2 Depth / Length | 26.5 in<br>673 mm |

## Additional Information

|                     |  |
|---------------------|--|
| Application         | For aluminum to copper, aluminum to aluminum or copper to copper magnet wire connections.  |
| Brand / Label       | Sta-Kon  |
| Effective Date      | 19700729   |
| Material            | Copper   |
| Number of Batteries | 0  |
| Product Name        | STA-KON AND CATAMOUNT TERMINAL   |
| Product Type        | Ring Terminal  |
| Special Functions   | Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire. |
| Standards           | UL E9809   |
| UPC                 | 786210878195   |

## Certificates and Declarations (Document Number)

|                                   |           |
|-----------------------------------|-----------|
| Data Sheet, Technical Information | 204210-1H |
| Instructions and Manuals          | 204210-1H |

## Classifications

|                                    |  |
|------------------------------------|--|
| ETIM 6                             | EC001052 - Solderless copper terminals for copper conductors |
| ETIM 7                             | EC001052 - Solderless copper terminals for copper conductors |
| UNSPSC                             | 39121432   |
| WEEE Category                      | Product Not in WEEE Scope                                    |
| IDEA Granular Category Code (IGCC) | 4603 >> Electrical terminals                                 |

## Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

