

PRODUCT-DETAILS

204210MT

INSUL PIERCING CONN CU 10-3 AWG



General Information

Extended Product Type	204210MT
Product ID	7TAI029010R0001
EAN	5414363111627
Catalog Description	INSUL PIERCING CONN CU 10-3 AWG
Long Description	Insulation Piercing Magnet Wire Modular Connector, Length Between Teeth .25 Inches, Length .92 Inches, Width .94 Inches, Wire Range #10 AWG - #3 AWG 90,000 Circular Mil Area - 215,000 Circular Mil Area, Copper Alloy, Tin Plated

Ordering

EAN	5414363111627
-----	---------------

Dimensions

Product Net Length	0, mm
--------------------	-------

Container Information

Package Level 2 Units	100 piece
Package Level 2 Width	7.5 in 191 mm
Package Level 2 Height	4.25 in 108 mm

Package Level 2 Depth / Length	10 in 254 mm
--------------------------------	-----------------

Additional Information	
Application	For aluminum to copper, aluminum to aluminum or copper to copper magnet wire connections.
Brand / Label	Sta-Kon
Effective Date	19721208
Material	Copper
Number of Batteries	0
Product Name	STA-KON AND CATAMOUNT TERMINAL
Product Type	Ring Terminal
Special Functions	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.
Standards	UL E9809
UPC	786210839257

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	204210MT
Instructions and Manuals	204210MT

Classifications	
ETIM 6	EC001059 - Crimp splices for copper conductor
ETIM 7	EC001059 - Crimp splices for copper conductor
UNSPSC	39121432
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4603 >> Electrical terminals

Categories
Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

