

76 mm

PRODUCT-DETAILS

204210SH

INSUL PRC DBL SPLICE CU 12-2 AWG



General Information	
Extended Product Type	204210SH
Product ID	7TAI029010R0003
EAN	5414363111634
Catalog Description	INSUL PRC DBL SPLICE CU 12-2 AWG
Long Description	Insulation Piercing Magnet Wire Double Splice, Length .69 Inches, Width .53 Inches, Height 1.05 Inches, Wire Range #12 AWG - #2 AWG 20,760 Circular Mil Area - 104,960 Circular Mil Area, Copper Alloy, Tin Plated
Ordering	
EAN	5414363111634
Product Net Length	0, mm
Froduct Net Length	0,11111
Container Information	
Package Level 1 Units	100 piece
Package Level 1 Width	4.5 in 114 mm
Package Level 1 Height	3 in

Package Level 1 Depth / Length	6 in 152 mm
Package Level 2 Units	500 piece
Package Level 2 Width	7 in
Dealisma Lavial 2 Hairiba	178 mm 8.7 in
Package Level 2 Height	8.7 III 221 mm
Package Level 2 Depth /	10.5 in
Length	267 mm

Additional Information		
Application	For aluminum to copper, aluminum to aluminum or copper to copper magnet wire connections.	
Brand / Label	Sta-Kon	
Effective Date	19700729	
Material	Copper	
Number of Batteries	0	
Product Name	STA-KON AND CATAMOUNT TERMINAL	
Product Type	Splice	
Special Functions	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.	
Standards	UL E9809	
Surface Finishing	Tin Plated	
UPC	786210870038	

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	204210SH	
Instructions and Manuals	204210SH	

Classifications		
ETIM 6	EC001059 - Crimp splices for copper conductor	
ETIM 7	EC001059 - Crimp splices for copper conductor	
UNSPSC	39121449	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice	

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Compression\ \&\ Mechanical\ Connectors$

204210SH 3

