

**SAIL-M12GM12G-S3-1.5P****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Your peripheral devices should be supplied with greater power. With our new M12 plug-in connector, more than 250 V and 2 A is possible without problems. The compact S- and T-coded M12 plug-in connectors are designed for the transmission of up to 630 V AC or 60 V DC and 12 A.

**General ordering data**

|            |                                                                                                                                                                        |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Power cable, Connecting line, Number of poles :<br>3 (2 + PE), 1.5 m, pin, straight - socket, straight,<br>Shielded: No, LED: No, Sheath material: PUR,<br>Halogen: No |
| Order No.  | <a href="#">2050060150</a>                                                                                                                                             |
| Type       | SAIL-M12GM12G-S3-1.5P                                                                                                                                                  |
| GTIN (EAN) | 4050118441260                                                                                                                                                          |
| Qty.       | 1 pc(s).                                                                                                                                                               |

Creation date March 26, 2021 9:58:49 PM CET

**SAIL-M12GM12G-S3-1.5P****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight 100 g

**Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

**Technical specifications for cable**

|                                                |                           |        |
|------------------------------------------------|---------------------------|--------|
| Acceleration                                   | 5 m/s²                    |        |
| Bending cycles                                 | 10 Mio                    |        |
| Bending radius, min., moving                   | 7.5 x cable diameter      |        |
| Bending radius, min., stationary               | 4 x cable diameter        |        |
| Cable length                                   | 1.5 m                     |        |
| Colour coding                                  | blue, brown, Green/yellow |        |
| Configurable cable length                      | No                        |        |
| Core cross-section                             | 1.5 mm²                   |        |
| Halogen                                        | No                        |        |
| Housing main material                          | PUR                       |        |
| Insulation                                     | PP                        |        |
| Number of poles                                | 3                         |        |
| Number of poles                                | 3 (2 + PE)                |        |
| Outer cladding in accordance with UL AWM style | 20234 (80 °C / 1000 V)    |        |
| Outside diameter                               | Diameter                  | 8.5 mm |
|                                                | Signs                     | ±      |
|                                                | Tolerance                 | 0.3 mm |
| Outside diameter                               | 8.5 mm ± 0.3 mm           |        |
| PE function                                    | Yes                       |        |
| Resistant to welding beads                     | No                        |        |
| Sheath material                                | PUR                       |        |
| Sheathing colour                               | black                     |        |
| Shielded                                       | No                        |        |
| Speed                                          | 5 m/s                     |        |
| Suitable for cable carriers                    | Yes                       |        |
| Temperature range, moving                      | -40...80 °C               |        |
| Temperature range, moving, max.                | 80 °C                     |        |
| Temperature range, moving, min.                | -40 °C                    |        |
| Temperature range, stationary                  | -50...80 °C               |        |
| Temperature range, stationary, max.            | 80 °C                     |        |
| Temperature range, stationary, min.            | -50 °C                    |        |

**General technical data**

|                              |              |                     |                                  |
|------------------------------|--------------|---------------------|----------------------------------|
| Coding                       | S            | Contact surface     | Gold-plated                      |
| Housing main material        | PUR          | Insulation strength | 10 <sup>8</sup> Ω                |
| LED                          | No           | Plugging cycles     | ≥ 100                            |
| Pollution severity           | 3            | Protection degree   | IP67, when screwed in            |
| Rated current                | 12 A         | Rated voltage       | 600 V                            |
| Temperature range of housing | -25...+80 °C | Version             | pin, straight - socket, straight |

**Standards**

Connector standard IEC 61076-2-111

Creation date March 26, 2021 9:58:49 PM CET

**SAIL-M12GM12G-S3-1.5P****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001855    | ETIM 7.0    | EC001855    |
| ECLASS 9.0  | 27-06-03-11 | ECLASS 9.1  | 27-06-03-11 |
| ECLASS 10.0 | 27-06-03-11 | ECLASS 11.0 | 27-06-03-11 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## SAIL-M12GM12G-S3-1.5P

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany


[www.weidmueller.com](http://www.weidmueller.com)

# Drawings


## Dimensioned drawing




## Dimensioned drawing




## Pole scheme



## Pole scheme



## Wiring diagram



## The ideal tool: Screwty® with torque function

