

PRODUCT-DETAILS

# 210214S

## INSUL PRC WIRE SPLICE CU 14-10 AWG



### General Information

Extended Product Type	210214S
Product ID	7TAI029010R0007
EAN	5414363077091
Catalog Description	INSUL PRC WIRE SPLICE CU 14-10 AWG
Long Description	Insulation Piercing Magnet Wire Splice, Length .63 Inches, Width .38 Inches, Height .37 Inches, Wire Range #14 AWG - #10 AWG 4,110 Circular Mil Area - 20,760 Circular Mil Area, Copper Alloy, Tin Plated

### Ordering

EAN	5414363077091
-----	---------------

### Dimensions

Product Net Length	0, mm
--------------------	-------

### Container Information

Package Level 1 Units	250 piece
Package Level 1 Width	4 in 102 mm
Package Level 1 Height	3 in 76 mm

Package Level 1 Depth / Length	4 in 102 mm
Package Level 2 Units	1250 piece
Package Level 2 Width	8.7 in 221 mm
Package Level 2 Height	6.9 in 175 mm
Package Level 2 Depth / Length	10.6 in 269 mm

---

### Additional Information

Application	For aluminum to copper, aluminum to aluminum or copper to copper magnet wire connections.
Brand / Label	Sta-Kon
Effective Date	19691010
Material	Copper
Number of Batteries	0
Product Name	ELECTRICAL TERMINAL
Product Type	Splice
Special Functions	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.
Standards	UL E9809
Surface Finishing	Tin Plated
UPC	786210867687

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	210214S
Instructions and Manuals	210214S

---

### Classifications

ETIM 6	EC001059 - Crimp splices for copper conductor
ETIM 7	EC001059 - Crimp splices for copper conductor
UNSPSC	39121449
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice

---

### Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

