

PRODUCT-DETAILS

220015

INSUL PRC WIRE SPLICE CU 10-6 AWG



Общая информация

Тип расширенного изделия	220015
Идентификационный номер изделия	7TAI029010R0010
Европейский товарный код (EAN)	5414363077107
Описание в каталоге	INSUL PRC WIRE SPLICE CU 10-6 AWG
Длинное описание	Insulation Piercing Magnet Wire Splice, Length 1.50 Inches, Width .88 Inches, Height .77 Inches, Wire Range #10 AWG - #6 AWG 50,000 Circular Mil Area - 115,000 Circular Mil Area, Copper Alloy, Tin Plated

Ordering

Европейский товарный код (EAN)	5414363077107
--------------------------------	---------------

Dimensions

Чистая длина изделия	0, mm
----------------------	-------

Container Information

Package Level 1 Units	50 штука
Package Level 1 Width	4 in 102 mm

Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	6 in 152 mm
Package Level 2 Units	250 штука
Package Level 2 Width	6.6 in 168 mm
Package Level 2 Height	5.2 in 132 mm
Package Level 2 Depth / Length	21.5 in 546 mm

Additional Information

Применение	For aluminum to copper, aluminum to aluminum or copper to copper magnet wire connections.
Торговая марка/ярлык	Sta-Kon
Дата вступления в силу	19730905
Материалы	Copper
Number of Batteries	0
Название изделия	STA-KON AND CATAMOUNT TERMINAL
Тип изделия	Splice
Специальные функции	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.
Стандарты	UL E9809
Surface Finishing	Tin Plated
Универсальный код товара (UPC)	786210855516

Certificates and Declarations (Document Number)

Технические данные	220015
Инструкции и руководства	220015

Classifications

ETIM 6	EC001059 - Crimp splices for copper conductor
ETIM 7	EC001059 - Crimp splices for copper conductor
Универсальная стандартная классификация товаров и услуг (UNSPSC)	39121449
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice

Категории

Низковольтное оборудование → Системы прокладки и защиты кабелей → Wire Management and Connectivity → Compression & Mechanical Connectors

