

PRODUCT-DETAILS

22L002

INSUL PRC WIRE SPLICE CU 24-15 AWG



General Information

Extended Product Type	22L002
Product ID	7TAI029030R0019
EAN	5414363112013
Catalog Description	INSUL PRC WIRE SPLICE CU 24-15 AWG
Long Description	Insulation Piercing Magnet Wire Splice, Length .32 Inches, Width .25 Inches, Height .19 Inches, Wire Range #24 AWG - #15 AWG 2,048 Circular Mil Area - 9,110 Circular Mil Area, Copper Alloy, Tin Plated

Ordering

EAN	5414363112013
-----	---------------

Dimensions

Product Net Length	0, mm
--------------------	-------

Container Information

Package Level 1 Units	1000 piece
Package Level 1 Width	4 in 102 mm
Package Level 1 Height	3 in 76 mm

Package Level 1 Depth / Length	4 in 102 mm
Package Level 2 Units	5000 piece
Package Level 2 Width	4.4 in 112 mm
Package Level 2 Height	3.5 in 89 mm
Package Level 2 Depth / Length	21.5 in 546 mm

Additional Information

Application	For aluminum to copper, aluminum to aluminum or copper to copper magnet wire connections.
Brand / Label	Sta-Kon
Effective Date	19770803
Material	Copper
Number of Batteries	0
Product Name	ELECTRICAL TERMINAL, SPLICE
Product Type	Splice
Special Functions	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.
Standards	UL E9809
Surface Finishing	Tin Plated
UPC	786210892474

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	22L002
Instructions and Manuals	22L002

Classifications

ETIM 6	EC001059 - Crimp splices for copper conductor
ETIM 7	EC001059 - Crimp splices for copper conductor
UNSPSC	39121449
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

