

PRODUCT-DETAILS

## 22L009H

## INSUL PRC DBL SPLICE CU 16-5 AWG



<b>General Information</b>	
Extended Product Type	22L009H
Product ID	7TAI029020R0017
EAN	5414363112051
Catalog Description	INSUL PRC DBL SPLICE CU 16-5 AWG
Long Description	Insulation Piercing Magnet Wire Double Splice, Length .32 Inches, Width .55 Inches, Height .93 Inches, Wire Range #16 AWG - #5 AWG 72,000 Circular Mil Area - 132,000 Circular Mil Area, Copper Alloy, Tin Plated
Ordering	
EAN	5414363112051
Dimensions	
Product Net Length	0, mm

Container Information		
Package Level 1 Units	100 piece	
Package Level 1 Width	4 in 102 mm	
Package Level 1 Height	4 in 102 mm	

Package Level 1 Depth / Length	6 in 152 mm
Package Level 2 Units	500 piece
Package Level 2 Width	8.7 in 221 mm
Package Level 2 Height	7.2 in 183 mm
Package Level 2 Depth / Length	10.4 in 264 mm

Additional Information	
Application	For aluminum to copper, aluminum to aluminum or copper to copper magnet wire connections.
Brand / Label	Sta-Kon
Effective Date	19841213
Material	Copper
Number of Batteries	0
Product Name	ELECTRICAL SPLICE
Product Type	Splice
Special Functions	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.
Standards	UL E9809
Surface Finishing	Tin Plated
UPC	786210782539

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	22L009H	
Instructions and Manuals	22L009H	

Classifications		
ETIM 6	EC001059 - Crimp splices for copper conductor	
ETIM 7	EC001059 - Crimp splices for copper conductor	
UNSPSC	39121449	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice	

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Compression\ \&\ Mechanical\ Connectors$ 

22L009H 3

