

PRODUCT-DETAILS

22LF01

INSUL PRC FEM DISCON CU 24-15 AWG



General Information

Extended Product Type	22LF01
Product ID	7TAI029030R0022
EAN	5414363112068
Catalog Description	INSUL PRC FEM DISCON CU 24-15 AWG
Long Description	Insulation Piercing Magnet Wire Female Disconnect, Length .79 Inches, Width .25 Inches, Length of Teeth .32 Inches, Width of Teeth .16 Inches, Tab Size .250 x .032, Wire Range #24 AWG - #15 AWG 404 Circular Mil Area - 4,100 Circular Mil Area, Copper Alloy, Tin Plated

Ordering

EAN	5414363112068
-----	---------------

Dimensions

Product Net Length	0, mm
--------------------	-------

Container Information

Package Level 1 Units	1000 piece
Package Level 1 Width	3.2 in 81 mm
Package Level 1 Height	4.69 in

	119 mm
Package Level 1 Depth / Length	6.3 in 160 mm
Package Level 2 Units	5000 piece
Package Level 2 Width	4.75 in 121 mm
Package Level 2 Height	3 in 76 mm
Package Level 2 Depth / Length	5 in 127 mm

Additional Information

Brand / Label	Sta-Kon
Effective Date	19801202
Material	Copper
Number of Batteries	0
Product Name	ELECTRICAL TERMINAL
Product Type	Disconnect
Special Functions	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.
Standards	UL E9809
Surface Finishing	Tin Plated
UPC	786210818634

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	22LF01
Instructions and Manuals	22LF01

Classifications

ETIM 6	EC001059 - Crimp splices for copper conductor
ETIM 7	EC001059 - Crimp splices for copper conductor
UNSPSC	39121447
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4667 >> Wire terminal disconnect

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

