

PRODUCT-DETAILS

22LF06

INSUL PRC FEM DISCON CU 16-12 AWG



General Information

Extended Product Type	22LF06
Product ID	7TAI029020R0018
EAN	5414363112075
Catalog Description	INSUL PRC FEM DISCON CU 16-12 AWG
Long Description	Insulation Piercing Magnet Wire Female Disconnect, Length .91 Inches, Width .25 Inches, Length of Teeth .45 Inches, Width of Teeth .25 Inches, Tab Size .250 x .032, Wire Range #16 AWG - #12 AWG 2,580 Circular Mil Area - 12,330 Circular Mil Area, Copper Alloy, Tin Plated

Ordering

EAN	5414363112075
-----	---------------

Dimensions

Product Net Length	0, mm
--------------------	-------

Container Information

Package Level 1 Units	1000 piece
Package Level 1 Width	4.5 in 114 mm
Package Level 1 Height	3 in

	76 mm
Package Level 1 Depth / Length	6 in 152 mm
Package Level 2 Units	5000 piece
Package Level 2 Width	9.7 in 246 mm
Package Level 2 Height	6.8 in 173 mm
Package Level 2 Depth / Length	16 in 406 mm

Additional Information

Application	For aluminum to copper, aluminum to aluminum or copper to copper magnet wire connections.
Brand / Label	Sta-Kon
Effective Date	19801202
Material	Copper
Number of Batteries	0
Product Name	ELECTRICAL TERMINAL
Product Type	Vinyl Insulated Female Disconnect
Special Functions	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.
Standards	UL E9809
Surface Finishing	Tin Plated
UPC	786210818658

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	22LF06
Instructions and Manuals	22LF06

Classifications

ETIM 6	EC001059 - Crimp splices for copper conductor
ETIM 7	EC001059 - Crimp splices for copper conductor
UNSPSC	39121447
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4667 >> Wire terminal disconnect

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

