

PRODUCT-DETAILS

22LM06

INSUL PRC MALE DISCON CU 16-12 AWG



General Information

Extended Product Type	22LM06
Product ID	7TAI029030R0023
EAN	5414363112099
Catalog Description	INSUL PRC MALE DISCON CU 16-12 AWG
Long Description	Insulation Piercing Magnet Wire Male Disconnect, Length .91 Inches, Width .25 Inches, Length of Teeth .45 Inches, Width of Teeth .25 Inches, Tab Size .250 x .032, Wire Range #16 AWG - #12 AWG 2,580 Circular Mil Area - 12,330 Circular Mil Area, Copper Alloy, Tin Plated

Ordering

EAN	5414363112099
-----	---------------

Dimensions

Product Net Length	0, mm
--------------------	-------

Container Information

Package Level 1 Units	1000 piece
Package Level 1 Width	4.5 in 114 mm
Package Level 1 Height	3 in

	76 mm
Package Level 1 Depth / Length	6 in 152 mm
Package Level 2 Units	5000 piece
Package Level 2 Width	6.5 in 165 mm
Package Level 2 Height	8.3 in 211 mm
Package Level 2 Depth / Length	10 in 254 mm

Additional Information

Brand / Label	Sta-Kon
Effective Date	19771228
Material	Copper
Number of Batteries	0
Product Name	STA-KON AND CATAMOUNT TERMINAL
Product Type	Male Disconnect
Special Functions	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.
Standards	UL E9809
Surface Finishing	Tin Plated
UPC	786210807805

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	22LM06
Instructions and Manuals	22LM06

Classifications

ETIM 6	EC001059 - Crimp splices for copper conductor
ETIM 7	EC001059 - Crimp splices for copper conductor
UNSPSC	39121447
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4667 >> Wire terminal disconnect

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

