

Repeater - PSI-REP-DNET CAN - 2313423

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Modular repeater for electrical isolation and increasing the range for DeviceNet/SDS/CANopen, data rate of up to 1 Mbps. High-quality electrical isolation between the interfaces, DIN-rail mountable, 24 V DC supply.

Product Description

The performance and availability of bus systems can be significantly increased by using repeaters. In addition to electrical isolation, bus segmentation with repeaters makes it possible to multiply the permissible coverage of the network and to extend the number of devices.

Your advantages

- ✓ Automatic data rate detection or fixed data rate setting via DIP switches
- ✓ Data rates of up to 1 Mbps
- ✓ High-quality 4-way isolation between all interfaces
- ✓ Can be combined with PSI-MOS FO converters in a modular way thanks to DIN rail connectors
- ✓ All connections can be plugged in using a COMBICON screw terminal block
- ✓ Approved for use in zone 2
- ✓ Shipbuilding approval in accordance with DNV GL



DeviceNet CANopen



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 428392
GTIN	4046356428392
Weight per Piece (excluding packing)	240.000 g
Custom tariff number	85176200
Country of origin	Germany