

Multiplexer - FB-MUX/HS/DIO-NAM/PA - 2316270

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The FB-MUX/HS/DIO-NAM/PA head station can be used with up to three 4-channel NAMUR digital input modules (RAD-NAM4-IFS) and two 4-channel digital output modules (RAD-DOR4-IFS). This configuration can be used as a valve coupler solution to open and close, as well as monitor, the position of a valve.

Product Description

The fieldbus PA multiplexer headstation allows the integration of standard Radioline I/O modules to a Profibus PA network. The FB-MUX/HS/PA has five profile software versions for different IO configurations.

Your advantages

- ✓ UL listed
- ✓ Suitable for ATEX Zone 2
- ✓ Scalable according to application needs
- ✓ Five application-specific head stations allow simple implementation in the field
- ✓ Easy integration into host system with an EDD-, GSD-, or DTM-data file
- ✓ IECEx CoC
- ✓ No software needed thanks to a pre-configured head station
- ✓ Connection of all I/O field signals with standard PROFIBUS PA cable



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 323305
GTIN	4055626323305
Weight per Piece (excluding packing)	0.010 g
Custom tariff number	85176200
Country of origin	United States