

Weidmüller Interface GmbH & Co. KG

SAID-M8B-3-THR

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Similar to illustration





Weidmüller is one of the industry's leading international providers of connectors. An important mainstay in this product family are the circular connectors, which Weidmüller groups under the product name SAI. In the development of SAI products, Weidmüller engineers have always concentrated on achieving rational, cost-effective installation concepts, and – in cooperation with major users – have supplied the markets with well-conceived products which set standards in terms of functionality and quality across the globe. The best examples are the new power distributors with S and T coded M12. These modules are characterised by particularly high currents and voltages. This enables them to also be used, for example, with three-phase motors.

General ordering data

Version	Built-in plugs, M8, Socket connector, M 12, Number of poles: 3	
Order No.	<u>2423760000</u>	
Туре	SAID-M8B-3-THR	
GTIN (EAN)	4050118430769	
Qty.	25 pc(s).	



SAID-M8B-3-THR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Not weight	2 22 4			
et weight 2.32 g				
Environmental Product	Compliance			
REACH SVHC	Lead 7439-92-1			
Technical data of PCB p	lug-in connector			
Coding	M8 = none	Housings	M8 socket	
Number of poles	3	Shield connection	No	
Rated voltage	60 V	Rated voltage (text)	60 V (3-pole) / 30 V (4-,5- and 8-pole)	
Rated current	4 A	Rated current	4 A (3-, 4- and 5-pole) / 1.5 A (8-pole)	
Temperature range	-2595 °C	Protection degree	IP67	
Contact surface	Au (Gold)	Housing main material	LCP	
Connection thread	M8	Tightening torque	M8: 0.5 Nm	
Insulation strength	100 ΜΩ	Pollution severity	3 (2 within the sealed area)	
Plugging cycles	≥ 100	Contact material	CuZn	
Lock nut material	Nickel-plated CuZn	Material of the flange-mounted housing	Nickel-plated CuZn	
General Info				
Housing main material	LCP	Connection thread	M8	
Contact material	CuZn	Contact surface	Au (Gold)	
Protection degree	IP67	Plugging cycles	≥ 100	
Material data				
Contact material	CuZn	Contact surface	Au (Gold)	
System parameters				
Insulation strength	100 ΜΩ	Number of poles	3	
Pin series quantity	1	Plugging cycles	≥ 100	
Protection degree	IP67	I lagging cycles	_ 100	
Classifications				
ETIM 6 O	EC000438	ETIM 7.0	EC002557	
ETIM 6.0 ECLASS 9.1	27-44-02-05	ETIM 7.0 ECLASS 10.0	EC003557 27-44-02-23	
ECLASS 9.1 ECLASS 11.0	27-44-02-23	LOLASS TO.O	<u> </u>	
Approvals				
ROHS	Conform			

Engineering Data

STEP



SAID-M8B-3-THR


Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany


www.weidmueller.com

Drawings

Dimensioned drawing



PCB design



Pole scheme

