

UR67-PN-HP-8IOL-12-60M**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****General ordering data**

Version	Automation Products - u-remote IP67, Sensor-actuator active distributor, PROFINET V2.3
Order No.	2426260000
Type	UR67-PN-HP-8IOL-12-60M
GTIN (EAN)	4050118434293
Qty.	1 pc(s).

UR67-PN-HP-8IOL-12-60M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	17.6 mm	Height (inches)	0.693 inch
Length	200 mm	Length (inches)	7.874 inch
Net weight	500 g	Width	59.6 mm
Width (inches)	2.346 inch		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Connections

Fieldbus (BUS-IN)	1x M12 female 4-pole, D-coded	Fieldbus (BUS-OUT)	1x M12 female 4-pole, D-coded
I/O connections	8 x M12 socket 5-pole, A-coded	Supply voltage (AUX-IN)	1x M12 plug 5-pole, L-coded
Supply voltage (AUX-OUT)	1x M12 socket 5-pole, L-coded		

Digital inputs

Diagnostic display	Per channel, via LED, red		
Digital inputs	Short-circuit protection	Yes	
	Overload protection	Yes	
	Reverse polarity protection	Yes	
Input current, high	Type 1 in acc. with IEC 61131-2		
Input current, low	Type 1 in acc. with IEC 61131-2		
Input type	P-switching		
Overload protection	Yes		
Short-circuit protection	Yes		
Status indicator	Per channel, via LED, yellow		

Digital outputs

Diagnostic display	Per channel, via LED, red		
Digital outputs	Short-circuit protection	Yes	
	Overload protection	Yes	
	Reverse polarity protection	Yes	
Max. total current outputs	9 A		
Output voltage, high	max. 2 V		
Output voltage, low	- 1 V		
Overload protection	Yes		
Short-circuit protection	Yes		
Status indicator	Per channel, via LED, yellow		
max. current-carrying capacity per output signal	0.5 A, 2 A		

General data

Housing main material	Zinc diecast	Module variants	IO link, 4 x type A, 4 x type B
Protection degree	IP67	UL 94 flammability rating	UL 94

UR67-PN-HP-8IOL-12-60M**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Supply voltage**

Limits	18 V DC ... 30 V DC	Operating voltage	24 V
Power consumption of module electronics	160 mA typical	Reverse polarity protection	Yes

Classifications

ETIM 6.0	EC001597	ETIM 7.0	EC001597
ECLASS 9.0	27-24-26-02	ECLASS 9.1	27-24-26-02
ECLASS 10.0	27-24-26-02	ECLASS 11.0	27-24-26-02

Approvals

Approvals



ROHS	Conform
UL File Number Search	E141197

Downloads

Approval/Certificate/Document of Conformity	UR67_EU Declaration of Conformity PN45
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
Software	UR67 - GSDML V2.33 / EDS V3.21 / ESI V1.2 files UR67 - GSDML V2.31 / EDS V3.9 / ESI V1.2 files
User Documentation	MAN UR67 IO-LINK EN MAN UR67 IO-LINK DE