

UR67-PB-78-16DI-12-60M**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****u-remote IP67 PROFIBUS-DP modules**

M12 or 7/8" feed-in; 30 & 60 mm wide housings

With over 43 million devices worldwide, PROFIBUS is the most widespread fieldbus. In the manufacturing industry, PROFIBUS-DP is used in the field for communication between control and sensor or actuator.

PROFIBUS enables simple and cost-saving topologies, bidirectional communication, extensive information and diagnosis options and standardised integration of devices and device functions via device master data files (DMD).

General ordering data

Version	Automation Products - u-remote IP67, Profibus-DP
Order No.	2426390000
Type	UR67-PB-78-16DI-12-60M
GTIN (EAN)	4050118434453
Qty.	1 pc(s).

UR67-PB-78-16DI-12-60M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	31 mm	Height (inches)	1.22 inch
Length	264.7 mm	Length (inches)	10.421 inch
Net weight	615 g	Width	59.6 mm
Width (inches)	2.346 inch		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Configuration

System integration	GSD file
--------------------	----------

Connections

Fieldbus (BUS-IN)	1x M12 plug 5-pole, B-coded	Fieldbus (BUS-OUT)	1x M12 female 5-pole, B-coded
I/O connections	8 x M12 socket 5-pole, A-coded	Supply voltage (AUX-IN)	1x 7/8" plug 5-pole
Supply voltage (AUX-OUT)	1x 7/8" socket 5-pole		

Digital inputs

Diagnostic display	Per channel, via LED, red	
Digital inputs	Short-circuit protection	Yes
	Overload protection	Yes
	Reverse polarity protection	Yes
Input current, high	2 mA to 15 mA in accordance with EN 61131-2 Type 1	
Input current, low	< 15 mA in accordance with EN 61131-2 Type 1	
Input filter	3 ms	
Status indicator	Per channel, yellow, white	

General data

Certificate	CE, cULus	Housing main material	Zinc diecast
Module variants	16 digital inputs	Protection degree	IP67
UL 94 flammability rating	UL 94		

Diagnosis

Channel	LED
---------	-----

Fieldbus

Addressing	Via rotary coding switch (1 – 126)	Bus system	Profibus-DP
Transmission rate	max. 12 Mbps (automatic detection)		

Supply voltage

Limits	18 V DC ... 30 V DC	Operating voltage	24 V
Power consumption of module electronics	60 mA typical		

UR67-PB-78-16DI-12-60M**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Classifications**

ETIM 6.0	EC001597	ETIM 7.0	EC001597
ECLASS 9.0	27-24-26-02	ECLASS 9.1	27-24-26-02
ECLASS 10.0	27-24-26-02	ECLASS 11.0	27-24-26-02

Approvals

Approvals



ROHS	Conform
UL File Number Search	E141197

Downloads

Approval/Certificate/Document of Conformity	UR67_EU Declaration of Conformity PN45
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
Software	UR67 - GSD files V1.03
User Documentation	MAN UR67 PB DE MAN UR67 PB EN