

IE-FCI-PWB-CZ**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Version	FrontCom, Insert Power large, Type E, Socket connector, CZ
Order No.	2426700000
Type	IE-FCI-PWB-CZ
GTIN (EAN)	4050118435139
Qty.	1 pc(s).

IE-FCI-PWB-CZ

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	29.35 g
------------	---------

Temperatures

Operating temperature	-5 °C...50 °C
-----------------------	---------------

General data

Connector face	Type E	Insert type	Insert Power large
Protection degree	IP20		

Clampable conductors

Conductor connection cross-section, extremely flexible with wire end ferrule	1.5 ... 1.5 mm ²
--	-----------------------------

Conductor connection cross-section, extremely flexible with wire end ferrule	min.	1.5 mm ²
	max.	1.5 mm ²

Conductor connection cross-section, extremely flexible without wire end ferrule	min.	1.5 mm ²
	max.	2.5 mm ²

Conductor connection cross-section, extremely flexible without wire end ferrule	1.5 ... 2.5 mm ²
---	-----------------------------

Conductor connection cross-section, flexible with wire end ferrule	1.5 ... 1.5 mm ²
--	-----------------------------

Conductor connection cross-section, flexible with wire end ferrule	min.	1.5 mm ²
	max.	1.5 mm ²

Conductor connection cross-section, flexible without wire end ferrule	max.	2.5 mm ²
	min.	1.5 mm ²

Conductor connection cross-section, flexible without wire end ferrule	1.5 ... 2.5 mm ²
---	-----------------------------

Conductor connection cross-section, rigid	1.5 ... 2.5 mm ²
---	-----------------------------

Conductor connection cross-section, rigid	min.	1.5 mm ²
	max.	2.5 mm ²

Stripping length	12 mm
------------------	-------

Type of connection	PUSH IN
--------------------	---------

Technical data

Housing main material	Polycarbonate PC	Rated current	16 A
Rated voltage (AC)	250 V		

Classifications

ETIM 6.0	EC001121	ETIM 7.0	EC001121
ECLASS 9.0	27-44-03-90	ECLASS 9.1	27-18-90-90
ECLASS 10.0	27-44-03-90	ECLASS 11.0	27-44-03-90

Approvals

ROHS	Conform
------	---------

IE-FCI-PWB-CZ

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Downloads

Engineering Data

[STEP](#)

User Documentation

[MAN IE GUIDE DE](#)

[MAN IE GUIDE EN](#)

[Socket Insert Overview EN](#)

[Socket Insert Overview DE](#)

[Designation key / Type key](#)


IE-FCI-PWB-CZ

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing



Dimensioned drawing

