

**HS 4.2-12.7/25 MM W****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The heat-shrinkable sleeve is printable on 2 sides and can be used for marking and insulating cables and wires. The flexible, heat-shrink material enables a firm, perfect fit around the conductor and therefore saves space.

**General ordering data**

|         |                                                                                                                     |
|---------|---------------------------------------------------------------------------------------------------------------------|
| Version | Conductor and cable markers, 4.2 - 12.7 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, white |
|---------|---------------------------------------------------------------------------------------------------------------------|

|           |                            |
|-----------|----------------------------|
| Order No. | <a href="#">2437710000</a> |
|-----------|----------------------------|

|      |                     |
|------|---------------------|
| Type | HS 4.2-12.7/25 MM W |
|------|---------------------|

|            |               |
|------------|---------------|
| GTIN (EAN) | 4050118461206 |
|------------|---------------|

|      |              |
|------|--------------|
| Qty. | 1,000 pc(s). |
|------|--------------|

|                    |                                                                                  |
|--------------------|----------------------------------------------------------------------------------|
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a> <a href="#">1140490000</a> |
|--------------------|----------------------------------------------------------------------------------|

Creation date March 26, 2021 11:38:43 PM CET

## HS 4.2-12.7/25 MM W

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |           |
|----------------|------------|-----------------|-----------|
| Depth          | 0.77 mm    | Depth (inches)  | 0.03 inch |
| Height         | 25.4 mm    | Height (inches) | 1 inch    |
| Net weight     | 0.6 g      | Width           | 20.9 mm   |
| Width (inches) | 0.823 inch |                 |           |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -55...135 °C |
|-----------------------------|--------------|

## General data

|                                   |              |                                   |                                                           |
|-----------------------------------|--------------|-----------------------------------|-----------------------------------------------------------|
| Colour                            | white        | Halogen                           | Yes                                                       |
| Material                          | Polyolefine  | Number per roll                   | 1,000                                                     |
| Operating temperature range       | -55...135 °C | Operating temperature range, max. | 135 °C                                                    |
| Operating temperature range, min. | -55 °C       | Recommended industries            | Plant manufacture, Energy, Device manufacturer, Machinery |
| Width                             | 20.9 mm      |                                   |                                                           |

## Conductor and cable markers

|                                   |                   |                                  |                        |
|-----------------------------------|-------------------|----------------------------------|------------------------|
| Conductor O.D.                    | 4.2 - 12.7 mm     | Conductor O.D., max.             | 12.7 mm                |
| Conductor O.D., min.              | 4.2 mm            | Conductor cross-section, max.    | 35 mm <sup>2</sup>     |
| Conductor cross-section, min.     | 6 mm <sup>2</sup> | Cross-section for connected wire | 6 - 35 mm <sup>2</sup> |
| Halogen                           | Yes               | Rate of shrinkage                | 3:1                    |
| Recommended shrinking temperature | 90 °C             |                                  |                        |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |                       |
|------------------|-----------------------|
| Engineering Data | <a href="#">EPLAN</a> |
|------------------|-----------------------|

### HS 4.2-12.7/25 MM W

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

