

**HS-HF 1.2-2.4/25 MM W****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The heat-shrinkable sleeve is printable on 2 sides and can be used for marking and insulating cables and wires. The flexible, heat-shrink material enables a firm, perfect fit around the conductor and therefore saves space.

**General ordering data**

|                    |                                                                                                                    |
|--------------------|--------------------------------------------------------------------------------------------------------------------|
| Version            | Conductor and cable markers, 1.2 - 2.4 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, white |
| Order No.          | <a href="#">2437830000</a>                                                                                         |
| Type               | HS-HF 1.2-2.4/25 MM W                                                                                              |
| GTIN (EAN)         | 4050118461282                                                                                                      |
| Qty.               | 2,000 pc(s).                                                                                                       |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a> <a href="#">1140490000</a>                                   |

Creation date March 26, 2021 11:39:37 PM CET

## HS-HF 1.2-2.4/25 MM W

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

|                |            |                 |           |
|----------------|------------|-----------------|-----------|
| Depth          | 0.77 mm    | Depth (inches)  | 0.03 inch |
| Height         | 25.4 mm    | Height (inches) | 1 inch    |
| Net weight     | 0.272 g    | Width           | 4.2 mm    |
| Width (inches) | 0.165 inch |                 |           |

### Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -55...105 °C |
|-----------------------------|--------------|

### General data

|                                   |             |                                   |              |
|-----------------------------------|-------------|-----------------------------------|--------------|
| Colour                            | white       | Halogen                           | No           |
| Material                          | Polyolefine | Operating temperature range       | -55...105 °C |
| Operating temperature range, max. | 105 °C      | Operating temperature range, min. | -55 °C       |
| Width                             | 4.2 mm      |                                   |              |

### Conductor and cable markers

|                                   |                      |                                  |                            |
|-----------------------------------|----------------------|----------------------------------|----------------------------|
| Conductor O.D.                    | 1.2 - 2.4 mm         | Conductor O.D., max.             | 2.4 mm                     |
| Conductor O.D., min.              | 1.2 mm               | Conductor cross-section, max.    | 0.5 mm <sup>2</sup>        |
| Conductor cross-section, min.     | 0.25 mm <sup>2</sup> | Cross-section for connected wire | 0.25 - 0.5 mm <sup>2</sup> |
| Halogen                           | No                   | Rate of shrinkage                | 2:1                        |
| Recommended shrinking temperature | 90 °C                |                                  |                            |

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                                             |                                                                                                                                               |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">NFX 70-100-1 2006 + NF X 70-100-2 2006</a><br><a href="#">BS EN 45545-2 2013+A1 2015</a><br><a href="#">BS EN ISO 4589-2 1999</a> |
| Engineering Data                            | <a href="#">EPLAN</a>                                                                                                                         |

### HS-HF 1.2-2.4/25 MM W

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

