

MCP BASIC 2**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The MCP Basic 2 is particularly suitable if you need to print small quantities of markers on site. It is particularly compact and, due to its low weight, can be used quickly anywhere. The MCP Basic 2 is perfect for marking small quantities of print media and reduces the amount of unused markers.

General ordering data

Version	Marking systems, Labelling device, Plotter printing with india ink, Multicard, Labels
Order No.	2438520000
Type	MCP BASIC 2
GTIN (EAN)	4050118465396
Qty.	1 pc(s).

MCP BASIC 2

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	155 mm	Depth (inches)	6.102 inch
Height	470 mm	Height (inches)	18.504 inch
Net weight	9,620 g	Width	480 mm
Width (inches)	18.898 inch		

Temperatures

Ambient temperature	10 °C- 35 °C
---------------------	--------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Labelling systems

Feeding		Included in delivery	MCP Basic 2, MultiCard mounting plate, Manuals (CD), Software M-Print® PRO, Plotter pen 0.25 P-INK, USB cable, Power supply (100–240 V AC / 50/60 Hz), Euro plug, US plug
	Manuall mounting		
Interface	USB	Marker type	Multicard, Labels
Operating system	Windows 7, Windows 8, Windows 8.1, Windows 10	Operation with rechargeable batteries	No
Printer driver	Windows 7, Windows 8, Windows 8.1, Windows 10	Printing method	Plotter printing with india ink
Printing speed	max. 40 cm/s	Software	M-Print® PRO
System requirements	PC with operating system Windows 7, 8 or 10	Type	MCP Basic 2
Voltage supply	100...240 V AC		

Classifications

ETIM 6.0	EC000610	ETIM 7.0	EC000610
ECLASS 9.0	24-32-11-90	ECLASS 9.1	24-32-11-02
ECLASS 10.0	24-32-11-90	ECLASS 11.0	24-32-11-90

Approvals

ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	Konformitätserklärung
Software	Driver for plotter
User Documentation	Manual