

FAD 1771-WB/WD SL12 M**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

With increasing plant complexity, the obsolescence of certain PLCs and the relentless growth in demand for I / O signals, many installations or plants are having to replace existing controllers with new ones, without modifying existing field cabling. With the aid of adapters, pre-assembled cables and interfaces from Weidmüller the problem of replacing one PLC system with another can be solved easily and safely: users can maintain the existing field cabling, test the new system and keep installation downtimes to a minimum.

General ordering data

Order No.	2448680000
Type	FAD 1771-WB/WD SL12 M
GTIN (EAN)	4050118462470
Qty.	1 pc(s).

FAD 1771-WB/WD SL12 M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	269 mm	Length (inches)	10.591 inch
Net weight	296.024 g	Width	32 mm
Width (inches)	1.26 inch		

Temperatures

Storage temperature	-40...60 °C	Operating temperature	-25...50 °C
---------------------	-------------	-----------------------	-------------

Connection data

Connection to PLC	SL 3.5/F 12p connector
-------------------	------------------------

Ratings data

Max. current per channel	2 A	Total operating current	6 A
--------------------------	-----	-------------------------	-----

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	< 300 V AC
Surge voltage category	II	Pollution severity level	2
Insulation test voltage	1.2 kVAC		

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
ECLASS 9.0	27-33-02-92	ECLASS 9.1	27-24-22-92
ECLASS 10.0	27-33-02-92	ECLASS 11.0	27-33-02-92

Approvals

Approvals



Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity
Engineering Data	EPLAN

FAD 1771-WB/WD SL12 M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

