

KEBI FS 606022 S2B0**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

For many years, the name Klippon® has stood for competence and quality in enclosures.

The Klippon® EBi industrial enclosure series protects your components reliably if they are used in moderate environmental conditions and is designed for everyday applications. With the ever-increasing need for individual application solutions, the Klippon® EBi with its high degree of protection and impact resistance is ideally suited to your needs.

Our standard product is the Klippon® EBi QL – with hinged door and double-bit key lock.

A variant with mounting screws is also available, but is only manufactured on request and is subject to a minimum order quantity. DNV GL and cULus approvals are also available on request.

General ordering data

Version	Klippon EBi FS (Essential Box industrial - Fixing Screw), Empty enclosure, stainless steel enclosure, Height: 600 mm, Width: 600 mm, Depth: 220 mm, Material: Stainless steel 1.4301 (304), Brushed, silver
Order No.	2471000000
Type	KEBI FS 606022 S2B0
GTIN (EAN)	4050118591408
Qty.	1 pc(s).

KEBI FS 606022 S2B0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	220 mm	Depth (inches)	8.661 inch
Diameter	9 mm	Height	600 mm
Height (inches)	23.622 inch	Mounting dimension - height	550 mm
Mounting dimension - width	550 mm	Net weight	16,800,000 g
Wall thickness, max.	1.5 mm	Wall thickness, min.	1.5 mm
Width	600 mm	Width (inches)	23.622 inch

Temperatures

Operating temperature	-40 °C...85 °C	Operating temperature range	-40 °C to 85 °C
-----------------------	----------------	-----------------------------	-----------------

Cable glands, left

M12	176	M16	96
M20	64	M25	39
M32	33	M40	16
M50	14	M63	5
M75	4		

Cable glands, right

M12	176	M16	96
M20	64	M25	39
M32	33	M40	16
M50	14	M63	5
M75	4		

Cable glands, top/bottom

M12	165	M16	96
M20	64	M25	39
M32	33	M40	16
M50	14	M63	5
M75	4		

Certificate numbers enclosure

Approval conditions	cULus	Certificate No. (DNVGL)	TAE00002RN
Certificate no. (cULus)	E256877	Declaration of Conformity No. (DoC LVD)	DE PS2650 180129 001ISS00

KEBI FS 606022 S2B0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

General information

Access opening: height	543 mm	Access opening: width	543 mm
Areas of use	Harbour facilities, Machine construction, Transportation, Marine engineering, Packaging industry, Process industry	Enclosure attachment	Fixing lugs, Installation through the housing rear wall
Flange plate	No	Impact resistance	10.00 J
Integral fixing	Screwed	Lid	Yes
Lid attachment	M6 torx stainless steel screws with slot, Removable cover + M6 screws	Material	Stainless steel 1.4301 (304)
Material thickness	1.5 mm	Material thickness of cover	1.5 mm
Material thickness of enclosure	1.5 mm	Material thickness of flange	1.5 mm
Number of lid screws	8	Operating temperature, max.	85 °C
Operating temperature, min.	-40 °C	Protection class (UL)	Type 3, Type 4x, Type 5
Protection degree	IP66	Seal material	Polyurethane foamed
Seal material of cover	Polyurethane foamed	Standards	DIN EN 62208, IEC 60529
Surface finish	Brushed	Torque for lid screws	2.5 Nm

Housing earth

Earth, enclosure, cover	Welded-on M6 stainless- steel earth stud in enclosure body and lid.	Earth, enclosure, external	M6 earth tab rivet
Earth, enclosure, internal	Welded-on M6 stainless- steel earth stud in enclosure body and lid.		

horizontal assembly

WDU 10 / ZDU 10	8x48	WDU 16 / ZDU 16	8x40
WDU 2,5 / ZDU 2,5 / IDU 2,5	8x94	WDU 35 / ZDU 35	8x30
WDU 4 / ZDU 4	8x79	WDU 6 / ZDU 6	8x60

vertical assembly

WDU 10 / ZDU 10	8x48	WDU 16 / ZDU 16	8x40
WDU 2,5 / ZDU 2,5 / IDU 2,5	8x94	WDU 35 / ZDU 35	8x30
WDU 4 / ZDU 4	8x79	WDU 6 / ZDU 6	8x60

Classifications

ETIM 6.0	EC000261	ETIM 7.0	EC000261
ECLASS 9.0	27-18-01-01	ECLASS 9.1	27-18-92-90
ECLASS 10.0	27-18-01-01	ECLASS 11.0	27-18-01-01

Important note

Product information	Minimum order quantity (50 pieces)
---------------------	------------------------------------

KEBI FS 606022 S2B0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS	Conform
UL File Number Search	E256877

Downloads

Approval/Certificate/Document of Conformity	TAE00002RN Declaration of Conformity
Engineering Data	EPLAN
User Documentation	Mounting Instructions Empty enclosures Klippon
Brochure/Catalogue	Catalogues in PDF-format

KEBI FS 606022 S2B0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing

