

HDC HP550 ABGH F185**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The protective housing is manufactured from seawater-resistant aluminium using pressure die casting. High standards of water and dust protection, as well as particularly high impact resistance, are the hallmarks of this housing series.

A sophisticated two-stage surface coating ensures years of reliability.

All screws, crimp contacts and other exterior accessory parts are made of corrosion-resistant stainless steel.

General ordering data

Version	HDC enclosures, Female, 1500 V, 550 A, Number of poles: 1, Crimp connection
Order No.	2486380000
Type	HDC HP550 ABGH F185
GTIN (EAN)	4050118497229
Qty.	1 pc(s).

HDC HP550 ABGH F185**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	80 mm	Depth (inches)	3.15 inch
Height	152 mm	Height (inches)	5.984 inch
Net weight	432.59 g	Width	60 mm
Width (inches)	2.362 inch		

Temperatures

Limit temperature	-40 °C ... 120 °C
-------------------	-------------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Dimensions

Width	60 mm
-------	-------

General data

Colour	black (similar to RAL 9005)	Conductor cross-section, max.	185 mm ²
Contact material	Copper alloy	Cross-section for connected wire	185 mm ²
Enclosure material	Aluminium diecast	Seal material	Silicone rubber
Series	HighPower	Surface finish	Powder coating
Type	Female	Type of connection	Crimp connection
Version insert	HighPower 550 A		

Classifications

ETIM 6.0	EC000437	ETIM 7.0	EC000437
ECLASS 9.0	27-44-02-02	ECLASS 9.1	27-44-02-02
ECLASS 10.0	27-44-02-02	ECLASS 11.0	27-44-02-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN
User Documentation	59000_HDC_HP550_ABGH_BG_00_BLATT.pdf