

UR20-1SM-50W-6DI2DO-P**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Pulse width modulation and stepper motor modules**

As part of the u-remote system, Weidmüller offers a specialised solution for controlling small motors with a current requirement of 0.5 A to 2 A, which can also be used to control valve flaps. The pulse width modulation modules can be adjusted within the switching frequencies up to 40 kHz and the modules can also be switched in the motor control with the aid of push/pull output stages, e.g. to change the direction of rotation.

Weidmüller's stepper motor module is efficient and flexible for use in the automation of robots, handling systems or placement machines with stepper motors. Variably adjustable operating parameters as well as a wide range supply from 12 V DC to 50 V DC make the module flexibly applicable for various target applications. Six integrated, parameterizable encoder or digital inputs and two digital outputs with 0.5 A make the control module a complete solution in the smallest of spaces.

As with all modules of the u-remote system, the features are convincing - from the modular design and exchangeable electronics to the removable and pluggable terminal strip. The module electronics supplies the connected actuators from the output current path (UOUT)

General ordering data

Version	Remote I/O module, IP20, Digital signals, Special module
Order No.	2489830000
Type	UR20-1SM-50W-6DI2DO-P
GTIN (EAN)	4050118499810
Qty.	1 pc(s).

UR20-1SM-50W-6DI2DO-P

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	76 mm	Depth (inches)	2.992 inch
Height	120 mm	Height (inches)	4.724 inch
Mounting dimension - height	128 mm	Net weight	173 g
Width	23 mm	Width (inches)	0.906 inch

Temperatures

Storage temperature	-40 °C ... +85 °C	Operating temperature	-20 °C ... +60 °C
---------------------	-------------------	-----------------------	-------------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

digital outputs

Actuator connection	2-wire	
Digital outputs	Connection designation	DO 0, DO 1
	Number of channels	2
	Response time high-low, max.	250 µs
	Response time low-high, max.	100 µs
	Output current per channel, max.	0.5 A
	Number of wires	2 Leiter
	Short-circuit-proof	Yes
	Reactionless	Yes
Feedback-free	Yes	
Individual channel diagnosis	No	
Inductive load (DC 13)	0.2 Hz	
Lamp load (12 W)	1 kHz	
Max. response time, high	250 µs	
Max. response time, low	100 µs	
Module diagnosis	Yes	
Number	1	
Number of digital outputs	2	
Outputs (as per IEC 61131-2)	2 digital outputs, 0.5 A, P-switching	
Protective circuit	Constant current with thermal switch-off and automatic restart	
Resistive load (min. 47 Ω)	1 kHz	
Sensor connection	2-wire, 3-wire	
Short-circuit-proof	Yes	
Switch-off energy (inductive)	< 150 mJ / channel	

Connection data

Number	1	
Stepper motor connections	Connection designation	A+, A-, B+, B-
	Number of channels	1
	Short-circuit-proof	Yes
Type of connection	PUSH IN	
Wire connection cross section, finely stranded, max.	1.5 mm²	
Wire connection cross section, finely stranded, min.	0.14 mm²	
Wire cross-section, finely stranded, max. AWG 16 (AWG)		
Wire cross-section, finely stranded, min. AWG 26 (AWG)		

Creation date April 15, 2021 10:19:30 PM CEST

UR20-1SM-50W-6DI2DO-P

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Wire cross-section, solid, max.	1.5 mm ²
Wire cross-section, solid, max. (AWG)	AWG 16
Wire cross-section, solid, min.	0.14 mm ²
Wire cross-section, solid, min. (AWG)	AWG 26

General data

Air humidity (operation)	10% to 95%, non-condensing as per DIN EN 61131-2		
Air humidity (storage)	10% to 95%, non-condensing as per DIN EN 61131-2		
Air humidity (transport)	10% to 95%, non-condensing as per DIN EN 61131-2		
Air pressure (operation)	≥ 795 hPa (height ≤ 2000 m) as per DIN EN 61131-2		
Air pressure (storage)	1013 hPa (height 0 m) to 700 hPa (height 3000 m) as per DIN EN 61131-2		
Air pressure (transport)	1013 hPa (height 0 m) to 700 hPa (height 3000 m) as per DIN EN 61131-2		
Pollution severity	2		
Rail	TS 35		
Restricted area	Positive expansion	Y coordinate	160 mm
		X coordinate	43 mm
		Z coordinate	85 mm
	Negative expansion	Y coordinate	-40 mm
		Z coordinate	0 mm
		X coordinate	-28 mm
	Type of restricted area	thermal	
Shock	15 g over 11 ms, half sinus wave, acc. to IEC 60068-2-27		
Surge voltage category	II		
Test voltage	500 V		
UL 94 flammability rating	V-0		
Vibration resistance	5 Hz ≤ f ≤ 8.4 Hz: 3.5-mm amplitude as per IEC 60068-2-6, 8.4 Hz ≤ f ≤ 150 Hz: 1 g acceleration as per IEC 60068-2-6		

Power supply

Current consumption from I _{IN} (power segment of the field bus coupler), typ.	8 mA	Current consumption from I _{OUT} (the respective power segment)	10 mA + load
Current consumption from external power supply	35 mA + load	Reverse polarity protection	Yes
Voltage supply	24 V DC +20 %/-15 %		

System data

Connection type	4-wire	Field bus protocol	PROFINET IRT, PROFINET RT, PROFIBUS DP-V1, EtherCAT, Modbus/TCP, EtherNet/IP, CANopen, DeviceNet, POWERLINK, CC-Link, CC-Link IE TSN
Galvanic isolation	500 V DC between the current paths	Interface	u-remote system bus
Transmission speed of system bus, max.	48 Mbit/s		

Classifications

ETIM 6.0	EC001601	ETIM 7.0	EC001601
ECLASS 9.0	27-24-26-05	ECLASS 9.1	27-24-26-05
ECLASS 10.0	27-24-26-05	ECLASS 11.0	27-24-26-05

UR20-1SM-50W-6DI2DO-P**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Approvals**

Approvals



ROHS	Conform
UL File Number Search	E141197

Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity
Engineering Data	STEP
Software	Current Firmware UR20-1SM-50W-6DI2DO-P
User Documentation	MANUAL - UR20 STEPPER MOTOR MODULE - EN HANDBUCH - UR20 SCHRITTMOTORMODUL - DE
Brochure/Catalogue	Catalogues in PDF-format