

HDC C MHX BM10.0AG**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Crimps provide a electrical and mechanical connection between wire and contact that is both secure and reliable. The optimal crimp connection is gas-tight and corrosion-resistant.

General ordering data

Version	Heavy-duty connectors, Crimp contact, Female, Conductor cross-section, max.: 10, turned, Copper alloy
Order No.	2494560000
Type	HDC C MHX BM10.0AG
GTIN (EAN)	4050118504538
Qty.	25 pc(s).

HDC C MHX BM10.0AG**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	2.78 g
------------	--------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Conductor cross-section, max.	10 mm ²	Contact diameter, male Ø	4 mm
Cross-section for connected wire	10 mm ²	Material	Copper alloy
Plugging cycles	≥ 500	Production methods	turned
Surface finish	silver	Type	Female
Type of connection	Crimp connection	Volume resistance	≤1 mΩ

Classifications

ETIM 6.0	EC000796	ETIM 7.0	EC000796
ECLASS 9.0	27-44-02-04	ECLASS 9.1	27-44-02-04
ECLASS 10.0	27-44-02-04	ECLASS 11.0	27-44-02-04

Important note

Product information	Stripping length 11 - 12 mm
---------------------	-----------------------------

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN

HDC C MHX BM10.0AG

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

