

**BLZP AH 12 BK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Example of use**

Similar to illustration

**Effective protection, optimised ergonomics and closed design:**

From the strain relief on the connected conductors and the visual/contact protection and the disconnection aid: the optional retrofit hoods perform mechanical, visual and haptic functions.

The two half shells clip together securely, enclose the plug completely and offer the following functions:

- Cable ties or integrated cable clips provide strain relief.
- Marked with dekafix labels or adhesive strips
- Mounting side by side without losing poles or displacing the pitch
- Compatible: suitable for plugs with or without a flange or mounting bracket
- Flexible: 1-3 cable outlets leading in different directions available depending on the size

Weidmüller hoods offer added stability, better identification, complete compatibility and versatility. The result: maximum reliability and user-friendliness in any application.

**General ordering data**

|              |                                                                |
|--------------|----------------------------------------------------------------|
| Version      | PCB plug-in connector, Accessories, black, Number of poles: 12 |
| Order No.    | <a href="#">2507140000</a>                                     |
| Type         | BLZP AH 12 BK                                                  |
| GTIN (EAN)   | 4050118524406                                                  |
| Qty.         | 10 pc(s).                                                      |
| Product data |                                                                |
| Packaging    | Box                                                            |

**BLZP AH 12 BK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Height         | 48 mm      | Height (inches) | 1.89 inch  |
| Length         | 60 mm      | Length (inches) | 2.362 inch |
| Net weight     | 21.1 g     | Width           | 19 mm      |
| Width (inches) | 0.748 inch |                 |            |

**Material data**

|                                       |          |                                       |        |
|---------------------------------------|----------|---------------------------------------|--------|
| Insulating material                   | PBT      | Colour                                | black  |
| Colour chart (similar)                | RAL 9011 | Storage temperature, min.             | -40 °C |
| Storage temperature, max.             | 70 °C    | Operating temperature, min.           | -50 °C |
| Operating temperature, max.           | 100 °C   | Temperature range, installation, min. | -25 °C |
| Temperature range, installation, max. | 100 °C   |                                       |        |

**Rated data acc. to IEC**

|                         |                        |
|-------------------------|------------------------|
| tested acc. to standard | IEC 60664-1, IEC 61984 |
|-------------------------|------------------------|

**Packing**

|           |        |            |        |
|-----------|--------|------------|--------|
| Packaging | Box    | VPE length | 160 mm |
| VPE width | 105 mm | VPE height | 50 mm  |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002943    | ETIM 7.0    | EC002943    |
| ECLASS 9.0  | 27-44-04-92 | ECLASS 9.1  | 27-44-04-92 |
| ECLASS 10.0 | 27-44-04-92 | ECLASS 11.0 | 27-46-04-05 |

**Important note**

|                |                                                                                                                                                                                                                                                                                                                            |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request. |
| Notes          | <ul style="list-style-type: none"> <li>Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months</li> </ul>                                                                                                                                                                   |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## BLZP AH 12 BK

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

