

SAIE-M12S-4-0.4U-AEH-VA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Various build-in connectors are required for the connections on the device side of the sensor/actuator cabling. These are available in the versions M12, M8 and M5.

General ordering data

Version	Built-in plugs, None, M12, pin, straight, None, PG 9, Number of poles: 4
Order No.	2512850000
Type	SAIE-M12S-4-0.4U-AEH-VA
GTIN (EAN)	4050118528008
Qty.	1 pc(s).

SAIE-M12S-4-0.4U-AEH-VA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	22 g
------------	------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data customisable plug-in connectors

Cable glands	None, PG 9	Coding	None, A
Contact surface	Gold-plated	Housing main material	None, Stainless steel, rust-proof
Number of poles	4	Plugging cycles	≥ 100
Pollution severity	3	Protection degree	None, IP67
Rated current	4 A	Rated voltage	250 V

General data

Cable glands	None, PG 9	Coding	None, A
Conductor O.D.	-	Connection thread	None, M12
Contact surface	Gold-plated	Core cross-section	0.34 mm ²
Housing main material	None, Stainless steel, rust-proof	Material	None, PVC
Mounting thread	PG 9	Number of poles	4
Plugging cycles	≥ 100	Pollution severity	3
Protection degree	None, IP67	Rated current	4 A
Rated voltage	250 V	Strand / cable length	0.4 m

Classifications

ETIM 6.0	EC002635	ETIM 7.0	EC003570
ECLASS 9.0	27-44-01-03	ECLASS 9.1	27-44-01-03
ECLASS 10.0	27-44-01-03	ECLASS 11.0	27-44-01-03

Approvals

ROHS	Conform
------	---------

SAIE-M12S-4-0.4U-AEH-VA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensional drawing

