

**HSS-HF 1.6-3.2 EL SW30M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The heat-shrinkable sleeve is printable on 2 sides and can be used for marking and insulating cables and wires. The flexible, heat-shrink material enables a firm, perfect fit around the conductor and therefore saves space.

**General ordering data**

|                    |                                                                                                                    |
|--------------------|--------------------------------------------------------------------------------------------------------------------|
| Version            | Conductor and cable markers, 1.6 - 3.2 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, black |
| Order No.          | <a href="#">2518920000</a>                                                                                         |
| Type               | HSS-HF 1.6-3.2 EL SW30M                                                                                            |
| GTIN (EAN)         | 4050118531121                                                                                                      |
| Qty.               | 1 pc(s).                                                                                                           |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a> <a href="#">1140490000</a>                                   |

Creation date March 29, 2021 6:27:22 PM CEST

**HSS-HF 1.6-3.2 EL SW30M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                |           |                 |              |
|----------------|-----------|-----------------|--------------|
| Depth          | 0.7 mm    | Depth (inches)  | 0.028 inch   |
| Length         | 30,000 mm | Length (inches) | 1,181.1 inch |
| Net weight     | 234 g     | Width           | 5.6 mm       |
| Width (inches) | 0.22 inch |                 |              |

**Temperatures**

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -55...105 °C |
|-----------------------------|--------------|

**General data**

|                                   |           |                                   |              |
|-----------------------------------|-----------|-----------------------------------|--------------|
| Colour                            | black     | Halogen                           | No           |
| Length                            | 30,000 mm | Material                          | Polyolefine  |
| Number per roll                   | 1         | Operating temperature range       | -55...105 °C |
| Operating temperature range, max. | 105 °C    | Operating temperature range, min. | -55 °C       |
| Width                             | 5.6 mm    |                                   |              |

**Conductor and cable markers**

|                                   |                     |                                  |                           |
|-----------------------------------|---------------------|----------------------------------|---------------------------|
| Conductor O.D.                    | 1.6 - 3.2 mm        | Conductor O.D., max.             | 3.2 mm                    |
| Conductor O.D., min.              | 1.6 mm              | Conductor cross-section, max.    | 1.5 mm <sup>2</sup>       |
| Conductor cross-section, min.     | 0.5 mm <sup>2</sup> | Cross-section for connected wire | 0.5 - 1.5 mm <sup>2</sup> |
| Halogen                           | No                  | Rate of shrinkage                | 2:1                       |
| Recommended shrinking temperature | 90 °C               |                                  |                           |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

**Important note**

|                     |                                           |
|---------------------|-------------------------------------------|
| Product information | External roll holder 1302920000 necessary |
|---------------------|-------------------------------------------|

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                                             |                                                                                                                                               |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">NFX 70-100-1 2006 + NF X 70-100-2 2006</a><br><a href="#">BS EN 45545-2 2013+A1 2015</a><br><a href="#">BS EN ISO 4589-2 1999</a> |
| Engineering Data                            | <a href="#">EPLAN</a>                                                                                                                         |

### HSS-HF 1.6-3.2 EL SW30M

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

