

KLIPPON BDX M20X15 S**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

General ordering data

Version	Klippon BDX (compensating elements), Compensating element, M 20, 15 mm, IP66, Stainless steel 1.4404 (316L)
Order No.	2519570000
Type	KLIPPON BDX M20X15 S
GTIN (EAN)	4050118532050
Qty.	1 pc(s).

KLIPPON BDX M20X15 S**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Length	22 mm	Length (inches)	0.866 inch
Net weight	60.2 g	Width	27 mm
Width (inches)	1.063 inch		

Certificate numbers cable gland

Approval conditions	ATEX, IECEX, EAC, UL AEx Class Div., UL AEx Class Zone	Certificate no. cable gland (ATEX)	SIRA 09ATEX3321X or CML 19ATEX3347X
Certificate no. cable gland (CSA)	2310046 or E340660	Certificate no. cable gland (EAC)	RU C-GB.FB06.B.00098 or RU C-GB.BH02.B.00693-18
Certificate no. cable gland (IECEX)	IECEX SIR 09.0132X or IECEX CML 19.0105X		

General information

AF size 1	27 mm	Air flow	0.25 l / 1 h
Explosion protection type	Improved safety Ex e	External thread	M 20
Filter	Bronze insert (90% copper, 10% tin)	Head diameter	26.2 mm
Impact resistance	7 J ATEX version	Length of thread	15 mm
Material		Note: protection class	- The venting element should be fitted on the bottom side of the enclosure, aligned vertically with the thread upwards, and at the lowest point to permit proper drainage. - The supplied assembly instructions must be read prior to installation and strictly adhered to. - The water flow rate was tested using a water-filled, empty enclosure (no pressure or heat-producing internal components). The water flow rate may vary due to operational parameters and environmental conditions.
	Stainless steel 1.4404 (316L)		
O-Ring	Silicone	Operating temperature range, max.	200 °C
Operating temperature range, min.	-60 °C	Pitch of thread	1.5 mm
Protection degree	IP66	Protection degree with GWDR	IP66
Sealing		Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31
	Silicone		
Tightening torque	10 Nm	Torque for connecting adapter, max.	10 Nm
Torque for connecting adapter, min.	10 Nm	Torque for lock nut, max.	10 Nm
Torque for lock nut, min.	10 Nm		

Classifications

ETIM 6.0	EC000814	ETIM 7.0	EC000814
ECLASS 9.0	27-14-44-25	ECLASS 9.1	27-14-44-90
ECLASS 10.0	27-14-44-25	ECLASS 11.0	27-14-44-25

KLIPPON BDX M20X15 S

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Downloads

Engineering Data

[STEP](#)

Engineering Data

[EPLAN](#)