

IE-FCI-PWB-ISR**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Version	FrontCom, Insert Power large, Type H, Socket connector, ISR
Order No.	2531060000
Type	IE-FCI-PWB-ISR
GTIN (EAN)	4050118541175
Qty.	1 pc(s).

Creation date March 29, 2021 6:51:51 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-FCI-PWB-ISR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	36.054 g
------------	----------

Temperatures

Operating temperature	-5 °C...50 °C
-----------------------	---------------

General data

Connector face	Type H	Insert type	Insert Power large
Protection degree	IP20		

Clampable conductors

Conductor connection cross-section, extremely flexible with wire end ferrule	1.5 ... 1.5 mm ²
--	-----------------------------

Conductor connection cross-section, extremely flexible with wire end ferrule	min.	1.5 mm ²
	max.	1.5 mm ²

Conductor connection cross-section, extremely flexible without wire end ferrule	...
---	-----

Conductor connection cross-section, flexible with wire end ferrule	1.5 ... 1.5 mm ²
--	-----------------------------

Conductor connection cross-section, flexible with wire end ferrule	min.	1.5 mm ²
	max.	1.5 mm ²

Conductor connection cross-section, flexible without wire end ferrule	...
---	-----

Conductor connection cross-section, rigid	1.5 ... 2.5 mm ²
---	-----------------------------

Conductor connection cross-section, rigid	min.	1.5 mm ²
	max.	2.5 mm ²

Stripping length	11 mm
------------------	-------

Type of connection	Screw connection
--------------------	------------------

Technical data

Housing main material	PP	Rated current	16 A
Rated voltage (AC)	250 V		

Classifications

ETIM 6.0	EC001121	ETIM 7.0	EC001121
ECLASS 9.0	27-44-03-90	ECLASS 9.1	27-18-90-90
ECLASS 10.0	27-44-03-90	ECLASS 11.0	27-44-03-90

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
User Documentation	Socket Insert Overview EN Socket Insert Overview DE Designation key / Type key


IE-FCI-PWB-ISR

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing



Dimensioned drawing

