

WIL-BM-SK-M12-3.0U**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Motion detector for the WIL-LED luminaire with screw connection, 3m supply cable and M12 cable for connection to the WIL lamp. Switching time adjustable.

General ordering data

Order No.	2537700000
Type	WIL-BM-SK-M12-3.0U
GTIN (EAN)	4050118549140
Qty.	1 pc(s).

WIL-BM-SK-M12-3.0U

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	44 mm	Depth (inches)	1.732 inch
Height	33 mm	Height (inches)	1.299 inch
Net weight	100 g	Width	76 mm
Width (inches)	2.992 inch		

Temperatures

Operating temperature	-20 - 60°C
-----------------------	------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Cable technical specifications

Cable Material	PUR	Sheathing colour	black
Cable length	3 m	Core cross-section	0.34 mm ²

Connection data

Coding	A	Connection thread	M12
Tightening torque	0.8 Nm	Wiring	PIN 4: + (black), PIN 3: - (blue)

Electric data

Rated voltage (text)	24 V DC	Rated current	< 6.0 A
----------------------	---------	---------------	---------

General technical data

Protection degree	IP20
-------------------	------

Classifications

ETIM 6.0	EC002955	ETIM 7.0	EC002955
ECLASS 11.0	27-11-06-92		

Approvals

Approvals



ROHS	Conform
------	---------

WIL-BM-SK-M12-3.0U

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

