

**HV2700/3-M12 F****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The efficient and reliable distribution of electrical power in a challenging environment requires interface solutions that are optimally designed for the special characteristics of a particular application. Perfect interplay is what you get with our high-current terminal solutions combined with Klippon® Protect enclosures in a weather-proof design.

Our HV 2700 und HV 4000 high-voltage terminals provide you with a modular and scalable system which, thanks to the ring cable lug connection system, is a globally recognised and proven railway technology and easy to install anywhere in the world. The products are tested and comply with the requirements of the technical standards EN 50155, EN 50124-1, EN 45545 and IEC 61373. Our products are subject to ongoing product monitoring and development.

We have put together a small selection for you, but we are happy to configure a bespoke solution.

**Customised installation**

The challenges for the future are reducing costs and increasing efficiency. This requires intelligent, individual solutions which are tailored to your requirements. In our application spectrum

we offer you a highly qualified customer-specific manufacturing service.

Whether you need modified products, pre-assembled terminal rails or complete small cabinets: we produce

the solutions developed for your application quickly and flexibly.

**General ordering data**

|            |                                                                    |
|------------|--------------------------------------------------------------------|
| Version    | Bolt-type screw terminals, Feed-through terminal, Screw connection |
| Order No.  | <a href="#">2540690000</a>                                         |
| Type       | HV2700/3-M12 F                                                     |
| GTIN (EAN) | 4050118554373                                                      |
| Qty.       | 1 pc(s).                                                           |

## HV2700/3-M12 F

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                            |            |                             |            |
|----------------------------|------------|-----------------------------|------------|
| Depth                      | 90 mm      | Depth (inches)              | 3.543 inch |
| Diameter                   | 11 mm      | Height                      | 220 mm     |
| Height (inches)            | 8.661 inch | Mounting dimension - height | 130 mm     |
| Mounting dimension - width | 215 mm     | Net weight                  | 4,800 g    |
| Width                      | 240 mm     | Width (inches)              | 9.449 inch |

## Temperatures

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 140 °C |
|----------------------------------|--------|----------------------------------|--------|

## Material data

|        |     |                           |     |
|--------|-----|---------------------------|-----|
| Colour | red | UL 94 flammability rating | V-0 |
|--------|-----|---------------------------|-----|

## Conductors for clamping (rated connection)

|                                                 |                          |                                                 |                     |
|-------------------------------------------------|--------------------------|-------------------------------------------------|---------------------|
| Cable lug to DIN 46234                          | 10...185 mm <sup>2</sup> | Clamping range, bolted connection , max.        | 185 mm <sup>2</sup> |
| Clamping range, bolted connection , min.        | 10 mm <sup>2</sup>       | Clamping range, max.                            | 185 mm <sup>2</sup> |
| Clamping range, min.                            | 10 mm <sup>2</sup>       | Clamping screw                                  | M 12                |
| Connection cross-section, finely stranded, max. | 185 mm <sup>2</sup>      | Connection cross-section, finely stranded, min. | 10 mm <sup>2</sup>  |
| Connection direction                            | top, Bottom              | Number of connections                           | 6                   |
| Stud size for spade connection                  | M 12                     | Tightening torque, max.                         | 35 Nm               |
| Tightening torque, min.                         | 33 Nm                    | Type of connection                              | Screw connection    |

## Dimensions

|          |       |
|----------|-------|
| Diameter | 11 mm |
|----------|-------|

## General

|           |                                                           |
|-----------|-----------------------------------------------------------|
| Standards | EN 45545-2:2020, NFPA 130 ASTM E 162/ 662, BSS 7239/ 7242 |
|-----------|-----------------------------------------------------------|

## Rating data

|                                          |                     |                                                  |                                                           |
|------------------------------------------|---------------------|--------------------------------------------------|-----------------------------------------------------------|
| Rated cross-section                      | 185 mm <sup>2</sup> | Rated voltage                                    | 2,700 V                                                   |
| Voltage with epoxy resin partition plate | 2,700 V             | Rated current                                    | 600 A                                                     |
| Current at maximum wires                 | 600 A               | Standards                                        | EN 45545-2:2020, NFPA 130 ASTM E 162/ 662, BSS 7239/ 7242 |
| Rated impulse withstand voltage          | 25 kV               | Impulse voltage with epoxy resin partition plate | 25 kV                                                     |
| Pollution severity                       | 3                   |                                                  |                                                           |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000897    | ETIM 7.0    | EC000897    |
| ECLASS 9.0  | 27-14-11-20 | ECLASS 9.1  | 27-14-11-20 |
| ECLASS 10.0 | 27-14-11-20 | ECLASS 11.0 | 27-14-11-20 |

### HV2700/3-M12 F

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

Brochure/Catalogue

[Catalogues in PDF-format](#)