


FF 67 54/230V GY**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The filter fans combine a safe and profitable cabinet cooling due to their low energy consumption by maximum air flow. The fluted filter mat of the IP 55 version extends the service life by up to 300% in comparison to conventional filter mats.

General ordering data

Version	Filter fan, IP54, grey
Order No.	2556950000
Type	FF 67 54/230V GY
GTIN (EAN)	4050118567571
Qty.	1 pc(s).

FF 67 54/230V GY

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	157 mm	Depth (inches)	6.181 inch
Height	320 mm	Height (inches)	12.598 inch
Net weight	3,700 g	Width	320 mm
Width (inches)	12.598 inch		

Temperatures

Operating temperature range	-40...55 °C
-----------------------------	-------------

General data

Colour	grey	
Current consumption	Mains frequency	50 Hz
	Current	0.62 A
	Mains frequency	60 Hz
	Current	0.86 A
EMC version	No	
Filter class	G 3	
Fuse	6 A	
Height of installation cut-outs	291 mm	
MTBF	40,000 h	
Mounting depth	150 mm	
Mounting height	7 mm	
Noise emission	66 dB (A)	
Operating temperature range	-40...55 °C	
Power	Mains frequency	50 Hz
	nominal	140 W
	Mains frequency	60 Hz
	nominal	197 W
Protection class (UL)	Type 12	
Rated voltage (text)	230 V AC ± 10%	
Size	6	
Type of connection	Spring contact	
Type of mounting	Snap-on	
UL 94 flammability rating	V-0	
Volume flow with exhaust filter	Mains frequency	50 Hz
	Volume flow	560 m³/h
	Exhaust filter	IP54
	Mains frequency	60 Hz
	Volume flow	625 m³/h
	Exhaust filter	IP54
Volume flow, free-blowing	Mains frequency	50 Hz
	Volume flow	845 m³/h
	Mains frequency	60 Hz
	Volume flow	875 m³/h
Volume flow, free-blowing at 50 Hz	845 m³/h	
Volume flow, free-blowing at 60 Hz	875 m³/h	
Width of installation cut-outs	291 mm	
With filter	Yes	

FF 67 54/230V GY**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Classifications**

ETIM 6.0	EC000320	ETIM 7.0	EC000320
ECLASS 9.1	27-18-07-16	ECLASS 10.0	27-18-07-16
ECLASS 11.0	27-18-07-16		

Approvals

Approvals



ROHS	Conform
UL File Number Search	E252704

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity
Engineering Data	STEP
User Documentation	Installation- and operating instructions


FF 67 54/230V GY

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Graph



Graph

