


**EF 30 55 BK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

The fluted filter mat of the IP 55 version extends the service life by up to 300% in comparison to conventional filter mats. Thought out details as the functional flap cover enable a fast and tool-less change of the filter mats which saves time and money.

**General ordering data**

|            |                             |
|------------|-----------------------------|
| Version    | Exhaust filter, IP55, black |
| Order No.  | <a href="#">2557160000</a>  |
| Type       | EF 30 55 BK                 |
| GTIN (EAN) | 4050118567793               |
| Qty.       | 1 pc(s).                    |

## EF 30 55 BK

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 40 mm      | Depth (inches)  | 1.575 inch |
| Height         | 202 mm     | Height (inches) | 7.953 inch |
| Net weight     | 260 g      | Width           | 202 mm     |
| Width (inches) | 7.953 inch |                 |            |

## Temperatures

|                             |             |
|-----------------------------|-------------|
| Operating temperature range | -40...55 °C |
|-----------------------------|-------------|

## General data

|                                |               |                                 |             |
|--------------------------------|---------------|---------------------------------|-------------|
| Colour                         | black         | EMC version                     | No          |
| Filter class                   | G 4           | Height of installation cut-outs | 177 mm      |
| Material                       | Thermoplastic | Mounting depth                  | 34 mm       |
| Mounting height                | 6 mm          | Operating temperature range     | -40...55 °C |
| Protection class (UL)          | Type 12       | Type of mounting                | Snap-on     |
| Width of installation cut-outs | 177 mm        | With filter                     | Yes         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002513    | ETIM 7.0    | EC002513    |
| ECLASS 9.1  | 27-18-07-06 | ECLASS 10.0 | 27-18-07-06 |
| ECLASS 11.0 | 27-18-07-06 |             |             |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E252704 |

## Downloads

|                    |                                                          |
|--------------------|----------------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                                     |
| User Documentation | <a href="#">Installation- and operating instructions</a> |