

IE-PI-SCRJ-POF-QA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



FO SC inserts for plug-in connectors ver.1 / 4 / 14

General ordering data

Version	SC insert, Plug SCRJ, POF, reconnectable
Order No.	2564960000
Type	IE-PI-SCRJ-POF-QA
GTIN (EAN)	4050118574647
Qty.	10 pc(s).

Creation date April 16, 2021 2:29:50 AM CEST

Catalogue status 09.04.2021 / We reserve the right to make technical changes.

IE-PI-SCRJ-POF-QA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	56 mm	Depth (inches)	2.205 inch
Height	10.5 mm	Height (inches)	0.413 inch
Net weight	1.6 g	Width	13.2 mm
Width (inches)	0.52 inch		

Temperatures

Operating temperature	-40 °C...70 °C
-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Colour	Miscellaneous	Configuration	Connector and flange insert for variant 1, 4 and 14 housings
Connection 1	SCRJ	Connection 2	Screw
Description of article	Plug SCRJ, POF, reconnectable	Dust protection cap material	TPE
Ferrule material	Arcap	Housing main material	PA 66
Insertion loss	≤ 1.0 dB	Plugging cycles	≥ 500
Protection degree	IP67 with housing	Sheath diameter, max.	8 mm
Sheath diameter, min.	5 mm	Single conductor diameter, max	2.3 mm
Single conductor diameter, min	2.1 mm	Type of mounting	Screw mounting

General standards

Connector standard	IEC 61754-24
--------------------	--------------

Classifications

ETIM 6.0	EC001122	ETIM 7.0	EC001122
ECLASS 9.0	19-17-01-22	ECLASS 9.1	19-17-01-22
ECLASS 10.0	19-17-01-22	ECLASS 11.0	19-17-01-22

Approvals

ROHS	Conform
------	---------

Downloads

User Documentation	Designation key / Type key
Brochure/Catalogue	Catalogues in PDF-format