

CRIMPFIX R VARIO**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

- For automatic stripping and crimping
- Time-saving and efficient processing
- Easily adjustable to the respective cross-section range
- Stripping and crimping in one work step
- The processing of sleeves or contacts from other manufacturers can cause machine failures and defects!

General ordering data

Version	Automatic stripper and crimper
Order No.	2580000000
Type	CRIMPFIX R VARIO
GTIN (EAN)	4050118605846
Qty.	1 pc(s).

CRIMPFIX R VARIO**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	485 mm	Depth (inches)	19.094 inch
Height	565 mm	Height (inches)	22.244 inch
Net weight	25,265 g	Weight	22 kg
Width	335 mm	Width (inches)	13.189 inch

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

PW65 maintenance - automatic stripping/crimping

Compressed-air connection	5.5 bar	Consumables	Linked wire-end ferrules
Crimping	Trapezoidal	Crimping length	8/10 mm
Drive	Electropneumatic	Electrical connection	100 - 240 V / 50/60 Hz / 16 VA
Insertion length, min.	27 mm	Length of wire-end ferrule	14/16 mm
Pulse time	approx. 2 s	Stripping range	0.5 - 2.5 mm ² (~AWG 20-14)
Wire end ferrules cross-section, max.	2.5 mm ²	Wire end ferrules cross-section, min.	0.5 mm ²

Classifications

ETIM 6.0	EC002778	ETIM 7.0	EC002778
ECLASS 9.0	17-13-01-01	ECLASS 9.1	17-13-01-01
ECLASS 10.0	17-13-01-01	ECLASS 11.0	17-13-01-01

Approvals

ROHS Conform

Downloads

User Documentation	Manual
Brochure/Catalogue	Catalogues in PDF-format