

CABTITE SE 2/6.5 SML GY**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

Whether a large or small cable diameter – Cabtite always offers the right seal insert.

The conical shape of the sealing elements allows the previously positioned snap-in grid inlays to be pushed in easily from the inside to the outside. It reliably seals intermediate spaces and provides strain relief in accordance with DIN EN 62444. The seal inserts combined with the frames achieve an IP 66 degree of protection. As a result of its slotted design with wave cut, it is especially suitable for pre-assembled cables.

- The black seal inserts are designed for a particularly high operating temperature and offer fire safety class UL 94 HB
- The grey sealing elements comply with fire safety class UL 94 V0 and are therefore suitable for the demands of the railway industry
- By using multiple inserts, two or more cables, as well as special cables, can be passed through a sealing element

General ordering data

Version	Sealing element, Cabtite (cable entry system), TPE, Light Grey, Height: 20.3 mm, Width: 20.3 mm, Depth: 17.7 mm, -40 °C...90 °C, IP54, IP65, IP66
Order No.	2584880000
Type	CABTITE SE 2/6.5 SML GY
GTIN (EAN)	4050118615531
Qty.	10 pc(s).

CABTITE SE 2/6.5 SML GY**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	17.7 mm	Depth (inches)	0.697 inch
Height	20.3 mm	Height (inches)	0.799 inch
Net weight	5.9 g	Width	20.3 mm
Width (inches)	0.799 inch		

Temperatures

Operating temperature	-40 °C...90 °C
-----------------------	----------------

General information

Halogen	No	Material	TPE
Outer cable diameter, max.	7 mm	Outer cable diameter, min.	6.5 mm
Sealing element	1 small sealing element	Silicone	No
UL 94 flammability rating	V-0		

Classifications

ETIM 6.0	EC000879	ETIM 7.0	EC000879
ECLASS 9.0	27-14-44-21	ECLASS 9.1	27-14-44-21
ECLASS 10.0	27-14-44-21	ECLASS 11.0	27-14-44-21

Approvals

Approvals



ROHS	Conform
UL File Number Search	E223801

Downloads

Engineering Data	STEP
Engineering Data	EPLAN
User Documentation	Cabtite Installation Instructions
Brochure/Catalogue	Catalogues in PDF-format