

**PRO COM IO-LINK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The power supply products can also be used universally in conjunction with our Industrial Ethernet, lightning and surge protection, relays and semiconductor switches, and can be combined to form many complete solutions.

**General ordering data**

| Version    | Communication module       |
|------------|----------------------------|
| Order No.  | <a href="#">2587360000</a> |
| Type       | PRO COM IO-LINK            |
| GTIN (EAN) | 4050118599152              |
| Qty.       | 1 pc(s).                   |

## PRO COM IO-LINK

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 33.6 mm | Depth (inches)  | 1.323 inch |
| Height     | 74.4 mm | Height (inches) | 2.929 inch |
| Net weight | 29 g    | Weight          | 29 g       |
| Width      | 35 mm   | Width (inches)  | 1.378 inch |

## Temperatures

|                       |                |
|-----------------------|----------------|
| Operating temperature | -25 °C...70 °C |
|-----------------------|----------------|

## Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

## General data

|                       |                |        |      |
|-----------------------|----------------|--------|------|
| Operating temperature | -25 °C...70 °C | Weight | 29 g |
|-----------------------|----------------|--------|------|

## Connection data (signal)

|                                      |                      |                                      |                     |
|--------------------------------------|----------------------|--------------------------------------|---------------------|
| Wire connection method               | PUSH IN              | Wire cross-section, AWG/kcmil , max. | 16                  |
| Wire cross-section, AWG/kcmil , min. | 26                   | Wire cross-section, solid , max.     | 1.5 mm <sup>2</sup> |
| Wire cross-section, solid , min.     | 0.14 mm <sup>2</sup> |                                      |                     |

## Approvals

|                         |         |                   |       |
|-------------------------|---------|-------------------|-------|
| Certificate no. (cULus) | E258476 | Institute (cULus) | CULUS |
|-------------------------|---------|-------------------|-------|

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| UL File Number Search | E258476 |
|-----------------------|---------|

## Downloads

|                                             |                                                                                                                                                                  |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">declaration of conformity</a>                                                                                                                        |
| Engineering Data                            | <a href="#">STEP</a>                                                                                                                                             |
| Software                                    | <a href="#">IO-Link IODD für topGUARD</a><br><a href="#">IO-Link IODD für PROtop</a>                                                                             |
| User Documentation                          | <a href="#">Instruction sheet</a><br><a href="#">IO-Link Register Description PROtop</a><br><a href="#">Addressing and IO-Link Register Description topGUARD</a> |
| Brochure/Catalogue                          | <a href="#">Catalogues in PDF-format</a>                                                                                                                         |