

**CD 100X60 4/6 GY****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**

The broad range of cable ducts offers you a flexible wire management system in a constant quality. The accurately sizes of the punched holes in accordance to DIN EN 50085-2-3 enables you a precise installation. Next to wire holding lugs as fixing aid for already installed wires, the optimal closing mechanism provide an easy snapping as well as a safe fit of the lid.

**General ordering data**

|            |                                                        |
|------------|--------------------------------------------------------|
| Version    | Cable duct, 100 mm x 60 mm, 4.00 mm x 6.00 mm, 2000 mm |
| Order No.  | <a href="#">2589330000</a>                             |
| Type       | CD 100X60 4/6 GY                                       |
| GTIN (EAN) | 4050118601428                                          |
| Qty.       | 16 m                                                   |

**CD 100X60 4/6 GY****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Height         | 100 mm     | Height (inches) | 3.937 inch |
| Length         | 2,000 mm   | Length (inches) | 78.74 inch |
| Net weight     | 994 g      | Width           | 60 mm      |
| Width (inches) | 2.362 inch |                 |            |

**Temperatures**

|                             |            |
|-----------------------------|------------|
| Operating temperature range | -5...60 °C |
|-----------------------------|------------|

**General information**

|                             |                                         |                           |                                 |
|-----------------------------|-----------------------------------------|---------------------------|---------------------------------|
| Colour                      | grey                                    | Flexible wiring duct      | No                              |
| Halogen                     | Yes                                     | Lid                       | Yes                             |
| Material                    | PVC / lead-free                         | Non-tracking              | Yes                             |
| Operating temperature range | -5...60 °C                              | Slit gap                  | 6 mm                            |
| Slit width                  | 4 mm                                    | Standards                 | In accordance with DIN EN 50085 |
| Type of mounting            | when screwed in, With adhesive, Riveted | UL 94 flammability rating | V-0                             |
| Usable cross-section        | 5,295 mm <sup>2</sup>                   | Version of side panel     | slotted                         |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000012    | ETIM 7.0    | EC000012    |
| ECLASS 9.1  | 27-40-07-03 | ECLASS 10.0 | 27-40-07-03 |
| ECLASS 11.0 | 27-40-07-03 |             |             |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E500004 |

**Downloads**

|                  |                      |
|------------------|----------------------|
| Engineering Data | <a href="#">STEP</a> |
|------------------|----------------------|

### CD 100X60 4/6 GY

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

