

CD-COD 90X90 4/6 GY

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com











The broad range of cable ducts offers you a flexible wire management system in a constant quality. The accurately sizes of the punched holes in accordance to DIN EN 50085-2-3 enables you a precise installation. Next to wire holding lugs as fixing aid for already installed wires, the optimal closing mechanism provide an easy snapping as well as a safe fit of the lid.

General ordering data

Version	Cable duct corner duct, 90 mm x 90 mm, 4.00 mm x 6.00 mm, 2000 mm
Order No.	<u>2589480000</u>
Туре	CD-COD 90X90 4/6 GY
GTIN (EAN)	4050118601275
Qty.	8 m



CD-COD 90X90 4/6 GY

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	90 mm	Height (inches)	3.543 inch
Length	2,000 mm	Length (inches)	78.74 inch
Net weight	1,438 g	Width	90 mm
Width (inches)	3.543 inch		

Temperatures

Operating temperature range	-560 °C
Oberating temperature range	-560 C

General information

Colour	grey	Flexible wiring duct	No
Halogen	Yes	Lid	Yes
Material	PVC / lead-free	Non-tracking	Yes
Operating temperature range	-560 °C	Slit gap	6 mm
Slit width		Standards	In accordance with DIN EN
	4 mm	_	50085
Type of mounting	when screwed in, With	UL 94 flammability rating	
	adhesive, Riveted		V-0
Usable cross-section	8,100 mm ²	Version of side panel	slotted

Classifications

ETIM 6.0	EC001942	ETIM 7.0	EC001942
ECLASS 9.1	27-40-07-07	ECLASS 10.0	27-40-07-07
ECLASS 11.0	27-40-07-07		

Approvals

ROHS	Conform	