

**CD-HF 75X75 5/7.5 LTGY****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**

The broad range of cable ducts offers you a flexible wire management system in a constant quality. The accurately sizes of the punched holes in accordance to DIN EN 50085-2-3 enables you a precise installation. Next to wire holding lugs as fixing aid for already installed wires, the optimal closing mechanism provide an easy snapping as well as a safe fit of the lid.

**General ordering data**

|            |  |
|------------|--|
| Version    | Halogen-free cable duct, 75 mm x 75 mm, 5.00 mm x 7.50 mm, 2000 mm |
| Order No.  | <a href="#">2589830000</a>   |
| Type       | CD-HF 75X75 5/7.5 LTGY   |
| GTIN (EAN) | 4050118603200  |
| Qty.       | 16 m   |

Creation date March 29, 2021 8:14:00 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**CD-HF 75X75 5/7.5 LTGY****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Height         | 75 mm      | Height (inches) | 2.953 inch |
| Length         | 2,000 mm   | Length (inches) | 78.74 inch |
| Net weight     | 675 g      | Width           | 75 mm      |
| Width (inches) | 2.953 inch |                 |            |

**Temperatures**

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -25...105 °C |
|-----------------------------|--------------|

**General information**

|                             |   |                           |                                 |
|-----------------------------|---|---------------------------|---------------------------------|
| Colour                      | Light Grey                              | Flexible wiring duct      | No                              |
| Halogen                     | No                                      | Lid                       | Yes                             |
| Material                    | PC-ABS                                  | Non-tracking              | Yes                             |
| Operating temperature range | -25...105 °C                            | Slit gap                  | 7.5 mm                          |
| Slit width                  | 5 mm                                    | Standards                 | In accordance with DIN EN 50085 |
| Type of mounting            | when screwed in, With adhesive, Riveted | UL 94 flammability rating | V-0                             |
| Usable cross-section        | 4,930 mm <sup>2</sup>                   | Version of side panel     | slotted                         |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000012    | ETIM 7.0    | EC000012    |
| ECLASS 9.1  | 27-40-07-03 | ECLASS 10.0 | 27-40-07-03 |
| ECLASS 11.0 | 27-40-07-03 |             |             |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E500004 |

**Downloads**

|                  |                      |
|------------------|----------------------|
| Engineering Data | <a href="#">STEP</a> |
|------------------|----------------------|

**Data sheet**

**CD-HF 75X75 5/7.5 LTGY**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

