

**CD 75X75 5/7.5 GY****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

The broad range of cable ducts offers you a flexible wire management system in a constant quality. The accurately sizes of the punched holes in accordance to DIN EN 50085-2-3 enables you a precise installation. Next to wire holding lugs as fixing aid for already installed wires, the optimal closing mechanism provide an easy snapping as well as a safe fit of the lid.

**General ordering data**

|            |                                                       |
|------------|-------------------------------------------------------|
| Version    | Cable duct, 75 mm x 75 mm, 5.00 mm x 7.50 mm, 2000 mm |
| Order No.  | <a href="#">2590180000</a>                            |
| Type       | CD 75X75 5/7.5 GY                                     |
| GTIN (EAN) | 4050118603224                                         |
| Qty.       | 16 m                                                  |

## CD 75X75 5/7.5 GY

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Height         | 75 mm      | Height (inches) | 2.953 inch |
| Length         | 2,000 mm   | Length (inches) | 78.74 inch |
| Net weight     | 744 g      | Width           | 75 mm      |
| Width (inches) | 2.953 inch |                 |            |

## Temperatures

|                             |            |
|-----------------------------|------------|
| Operating temperature range | -5...60 °C |
|-----------------------------|------------|

## General information

|                             |                                         |                           |                                 |
|-----------------------------|-----------------------------------------|---------------------------|---------------------------------|
| Colour                      | grey                                    | Flexible wiring duct      | No                              |
| Halogen                     | Yes                                     | Lid                       | Yes                             |
| Material                    | PVC / lead-free                         | Non-tracking              | Yes                             |
| Operating temperature range | -5...60 °C                              | Slit gap                  | 7.5 mm                          |
| Slit width                  | 5 mm                                    | Standards                 | In accordance with DIN EN 50085 |
| Type of mounting            | when screwed in, With adhesive, Riveted | UL 94 flammability rating | V-0                             |
| Usable cross-section        | 4,930 mm <sup>2</sup>                   | Version of side panel     | slotted                         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000012    | ETIM 7.0    | EC000012    |
| ECLASS 9.1  | 27-40-07-03 | ECLASS 10.0 | 27-40-07-03 |
| ECLASS 11.0 | 27-40-07-03 |             |             |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E500004 |

## Downloads

|                  |                      |
|------------------|----------------------|
| Engineering Data | <a href="#">STEP</a> |
|------------------|----------------------|

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

## Drawings