

THM MULTIMARK**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

These printers produce excellent printing results thanks to the thermal transfer technique. Different materials and the user-friendly printing system under Windows optimise marking efforts.

General ordering data

Version	Marking systems, Thermotransfer printer, Thermotransfer, 300 DPI, MultiMark, Shrink-fit sleeves, Label reel
Order No.	2599430000
Type	THM MULTIMARK
GTIN (EAN)	4050118626377
Qty.	1 pc(s).

THM MULTIMARK

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	253 mm	Depth (inches)	9.961 inch
Height	320 mm	Height (inches)	12.598 inch
Net weight	5,800 g	Weight	4 kg
Width	253 mm	Width (inches)	9.961 inch

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Labelling systems

Included in delivery	THM MultiMark, Manual, USB cable, Mains cable, Euro plug, US plug, UK plug, Printer driver, Software M-Print® PRO, RIBBON MM-TB 25/360 SW ink ribbon, RIBBON MM 110/360 SW ink ribbon, Ink ribbon core, Print roller, Pressure roller	Interface	USB 2.0, Ethernet
Marker type	MultiMark, Shrink-fit sleeves, Label reel	Operating system	Windows 7, Windows 8, Windows 8.1, Windows 10
Operation with rechargeable batteries	No	Print resolution, max.	300 DPI
Printing method	Thermotransfer	Printing speed	max. 150 mm/s
Software	M-Print® PRO	System requirements	PC with operating system Windows 7, 8 or 10
Type	THM MultiMark	Voltage supply	100...240 V AC

Classifications

ETIM 6.0	EC000610	ETIM 7.0	EC000610
ECLASS 9.0	24-32-11-90	ECLASS 9.1	24-32-11-02
ECLASS 10.0	24-32-11-90	ECLASS 11.0	24-32-11-90

Approvals

ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	China RoHS Declaration Declaration of Conformity
User Documentation	THM MULTIMARK