

**TRP 230VUC 1CO AU****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Similar to illustration

- 1 CO contact
- Contact material: AgNi 5µm Au
- Unique multi-voltage input from 24 to 230 V UC
- Input voltages from 5 V DC to 230 V UC with coloured marking: AC: red, DC: blue, UC: white

**General ordering data**

|            |                                                                                                                                                                              |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | TERMSERIES, Relay module, Number of contacts: 1, CO contact AgNi gold-plated, Rated control voltage: 230 V UC $\pm 10\%$ , Continuous current: 6 A, PUSH IN, Test button: No |
| Order No.  | <a href="#">2618210000</a>                                                                                                                                                   |
| Type       | TRP 230VUC 1CO AU                                                                                                                                                            |
| GTIN (EAN) | 4050118670622                                                                                                                                                                |
| Qty.       | 10 pc(s).                                                                                                                                                                    |

Creation date April 16, 2021 5:02:21 AM CEST

Catalogue status 09.04.2021 / We reserve the right to make technical changes.

## TRP 230VUC 1CO AU

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 87.8 mm    | Depth (inches)  | 3.457 inch |
| Height         | 89.4 mm    | Height (inches) | 3.52 inch  |
| Net weight     | 29 g       | Width           | 6.4 mm     |
| Width (inches) | 0.252 inch |                 |            |

## Temperatures

|                     |                                                                            |                       |                |
|---------------------|----------------------------------------------------------------------------|-----------------------|----------------|
| Storage temperature | -40 °C...85 °C                                                             | Operating temperature | -40 °C...60 °C |
| Humidity            | 5-95% relative humidity,<br>T <sub>u</sub> = 40°C, without<br>condensation |                       |                |

## Rated data UL

|                                    |                                                      |                                         |        |
|------------------------------------|------------------------------------------------------|-----------------------------------------|--------|
| Operating altitude                 | ≤ 2000 m, above sea level                            | Ambient temperature (operational), max. | 60 °C  |
| Connection cross-section AWG, min. | AWG 26                                               | Connection cross-section AWG, max.      | AWG 14 |
| Type of conductor                  | rigid copper conductor,<br>flexible copper conductor | Pollution severity level                | 2      |

## Control side

|                                       |                                          |                                                                                   |                                    |
|---------------------------------------|------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------|
| Coil voltage of the replacement relay | 60 V DC                                  | Coil voltage of the replacement relay<br>deviating from the rated control voltage | Yes                                |
| Power rating                          | 670 mW, 805 mVA                          | Protective circuit                                                                | Rectifier                          |
| Pull-in/drop-out current, typ.        | 2.4 mA / 0.9 mA AC<br>1.8 mA / 0.4 mA DC | Pull-in/drop-out voltage, typ.                                                    | 164 V / 87 V AC<br>166 V / 89 V DC |
| Rated control voltage                 | 230 V UC ± 10 %                          | Rated current AC                                                                  | 3.5 mA                             |
| Rated current DC                      | 2.9 mA                                   | Status indicator                                                                  | Green LED                          |

## Load side

|                                         |              |                            |              |
|-----------------------------------------|--------------|----------------------------|--------------|
| AC switching capacity (resistive), max. | 1500 VA      | Continuous current         | 6 A          |
| DC switching capacity (resistive), max. | 144 W @ 24 V | Inrush current             | 20 A / 20 ms |
| Max. switching frequency at rated load  | 0.1 Hz       | Max. switching voltage, DC | 250 V        |
| Min. switching power                    | 1 mA @ 1 V   | Rated switching voltage    | 250 V AC     |
| Switch-off delay                        | ≤ 45 ms      | Switch-on delay            | ≤ 14.5 ms    |

## Contact data

|              |                                 |                         |                                      |
|--------------|---------------------------------|-------------------------|--------------------------------------|
| Contact type | 1 CO contact (AgNi gold-plated) | Mechanical service life | 5 x 10 <sup>6</sup> switching cycles |
|--------------|---------------------------------|-------------------------|--------------------------------------|

## General data

|                                      |                          |                |  |
|--------------------------------------|--------------------------|----------------|--|
| Rail                                 | TS 35                    |                |  |
| Test button                          | No                       |                |  |
| Mechanical switch position indicator | No                       |                |  |
| Colour                               | black                    |                |  |
| UL94 flammability rating component   | Component                | Housing        |  |
|                                      | UL94 flammability rating | V-0            |  |
|                                      | Component                | Retaining clip |  |
|                                      | UL94 flammability rating | V-0            |  |
|                                      | Component                | Pusher         |  |
|                                      | UL94 flammability rating | V-0            |  |

## TRP 230VUC 1CO AU

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Insulation coordination

|                                                               |                             |                                                  |                              |
|---------------------------------------------------------------|-----------------------------|--------------------------------------------------|------------------------------|
| Clearance and creepage distances for control side - load side | ≥ 5.5 mm                    | Dielectric strength for control side - load side | 4 kV <sub>eff</sub> / 1 Min. |
| Dielectric strength of open contact                           | 1 kV <sub>eff</sub> / 1 min | Dielectric strength to mounting rail             | 4 kV <sub>eff</sub> / 1 Min. |
| Impulse withstand voltage                                     | 6 kV (1.2/50 μs)            | Pollution severity                               | 2                            |
| Protection degree                                             | IP20                        | Rated voltage                                    | 300 V                        |
| Surge voltage category                                        | III                         |                                                  |                              |

## Further details of approvals / standards

|                         |                                        |                         |            |
|-------------------------|----------------------------------------|-------------------------|------------|
| Standards               | EN 50178, EN 55011, EN 61000-6-1, 2, 4 | Certificate No. (DNVGL) | TAA00001E5 |
| Certificate no. (cULus) | E141197                                |                         |            |

## Connection data

|                                                                                         |                     |                                                                                         |                      |
|-----------------------------------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------|----------------------|
| Wire connection method                                                                  | PUSH IN             | Stripping length, rated connection                                                      | 9 mm                 |
| Clamping range, rated connection                                                        | 1.5 mm <sup>2</sup> | Clamping range, min.                                                                    | 0.14 mm <sup>2</sup> |
| Clamping range, max.                                                                    | 2.5 mm <sup>2</sup> | Wire connection cross section AWG, min.                                                 | AWG 26               |
| Wire connection cross section AWG, max.                                                 | AWG 14              | Wire cross-section, solid, min.                                                         | 0.14 mm <sup>2</sup> |
| Wire cross-section, solid, max.                                                         | 2.5 mm <sup>2</sup> | Wire cross-section, solid, min. (AWG)                                                   | AWG 26               |
| Wire cross-section, solid, max. (AWG)                                                   | AWG 14              | Wire connection cross section, finely stranded, min.                                    | 0.14 mm <sup>2</sup> |
| Wire connection cross section, finely stranded, max.                                    | 2.5 mm <sup>2</sup> | Wire cross-section, finely stranded, min. (AWG)                                         | AWG 26               |
| Wire cross-section, finely stranded, max. (AWG)                                         | AWG 14              | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.15 mm <sup>2</sup> |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 1.5 mm <sup>2</sup> | Conductor cross-section, flexible, AEH (DIN 46228-1), min.                              | 0.15 mm <sup>2</sup> |
| Conductor cross-section, flexible, AEH (DIN 46228-1), max.                              | 1.5 mm <sup>2</sup> | Twin wire-end ferrules, min.                                                            | 0.5 mm <sup>2</sup>  |
| Twin wire-end ferrules, max.                                                            | 1 mm <sup>2</sup>   | Blade size                                                                              | 0.4 x 2.0 mm         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001437    | ETIM 7.0    | EC001437    |
| ECLASS 9.0  | 27-37-16-01 | ECLASS 9.1  | 27-37-16-01 |
| ECLASS 10.0 | 27-37-16-01 | ECLASS 11.0 | 27-37-16-01 |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E141197 |

### TRP 230VUC 1CO AU

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                                             |                                                                         |
|---------------------------------------------|-------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EU Konformitätserklärung / EU Declaration of Conformity</a> |
| Engineering Data                            | <a href="#">STEP</a>                                                    |
| User Documentation                          | <a href="#">Beipackzettel / Package Insert – multilingual</a>           |
| Brochure/Catalogue                          | <a href="#">Catalogues in PDF-format</a>                                |


## TRP 230VUC 1CO AU

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany


[www.weidmueller.com](http://www.weidmueller.com)

## Drawings


### Wiring diagram



### Graph




### Graph



Electrical service life 230 V AC resistive load  
230 V AC resistive load

### Dimensional drawing



[www.weidmueller.com](http://www.weidmueller.com)