

AAM 1.5 YE FLASH**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Version	Terminal marker, 6.2 x 3.5 mm, yellow
Order No.	2635520000
Type	AAM 1.5 YE FLASH
GTIN (EAN)	4050118674088
Qty.	40 pc(s).

AAM 1.5 YE FLASH**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Depth	4.8 mm	Depth (inches)	0.189 inch
Height	6.2 mm	Height (inches)	0.244 inch
Net weight	0.061 g	Width	3.5 mm
Width (inches)	0.138 inch		

Temperatures

Operating temperature range	-40...100 °C
-----------------------------	--------------

Material data

Material	PA 6.6	Colour	yellow
UL 94 flammability rating	V-2		

Rating data IECEx/ATEX

Operating temperature range	-40...100 °C
-----------------------------	--------------

General

Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
-----------------------------------	--------	-----------------------------------	--------

Classifications

ETIM 6.0	EC000761	ETIM 7.0	EC000761
ECLASS 9.0	27-14-11-37	ECLASS 9.1	27-14-11-37
ECLASS 10.0	27-14-11-37	ECLASS 11.0	27-28-11-01

Downloads

Brochure/Catalogue	Catalogues in PDF-format
--------------------	--