



❗ Discontinued

Commercial status

Discontinued: 20 March 2019

Main

Range of product	Multi 9
Product or component type	Shunt trip release
Device short name	MX
[Uc] control circuit voltage	12...24 V AC 50/60 Hz 12...24 V DC
9 mm pitches	2

Complementary

Range compatibility	Multi 9 ID Multi 9 N40 Multi 9 C60 C60CTRL
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	73.5 mm 68 mm
Net weight	0.06 kg
Connections - terminals	Clamp terminal - 2 cable(s) 1.5 mm ² - flexible Clamp terminal - 1 cable(s) 0.5...2.5 mm ² - rigid Clamp terminal - 2 cable(s) 1.5 mm ² - flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA KEMA ASTA

LCIE

Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

26478 is replaced by:



electrical auxiliaries M9A26478

Multi 9 - shunt trip release - MX - 12/24 V AC - 12/24 V DC

Qty 1

Reason for Substitution: End of life | Substitution date: 27 March 2019